

Exam Code: SY0-701
Exam Name: CompTIA Security+



Exam A

QUESTION 1

A technician is opening ports on a firewall for a new system being deployed and supported by a SaaS provider. Which of the following is a risk in the new system?

- A. Default credentials
- B. Non-segmented network
- C. Supply chain vendor
- D. Vulnerable software

Correct Answer: C

Section:

Explanation:

A supply chain vendor is a third-party entity that provides goods or services to an organization, such as a SaaS provider. A supply chain vendor can pose a risk to the new system if the vendor has poor security practices, breaches, or compromises that could affect the confidentiality, integrity, or availability of the system or its data. The organization should perform due diligence and establish a service level agreement with the vendor to mitigate this risk. The other options are not specific to the scenario of using a SaaS provider, but rather general risks that could apply to any system.

QUESTION 2

Which of the following security concepts is the best reason for permissions on a human resources fileshare to follow the principle of least privilege?

- A. Integrity
- B. Availability
- C. Confidentiality
- D. Non-repudiation



Correct Answer: C

Section:

Explanation:

Confidentiality is the security concept that ensures data is protected from unauthorized access or disclosure. The principle of least privilege is a technique that grants users or systems the minimum level of access or permissions that they need to perform their tasks, and nothing more. By applying the principle of least privilege to a human resources fileshare, the permissions can be restricted to only those who have a legitimate need to access the sensitive data, such as HR staff, managers, or auditors. This can prevent unauthorized users, such as hackers, employees, or contractors, from accessing, copying, modifying, or deleting the data. Therefore, the principle of least privilege can enhance the confidentiality of the data on the fileshare. Integrity, availability, and non-repudiation are other security concepts, but they are not the best reason for permissions on a human resources fileshare to follow the principle of least privilege. Integrity is the security concept that ensures data is accurate and consistent, and protected from unauthorized modification or corruption. Availability is the security concept that ensures data is accessible and usable by authorized users or systems when needed. Non-repudiation is the security concept that ensures the authenticity and accountability of data and actions, and prevents the denial of involvement or responsibility. While these concepts are also important for data security, they are not directly related to the level of access or permissions granted to users or systems.

Reference: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, page 16-17, 372-373

QUESTION 3

A company is planning to set up a SIEM system and assign an analyst to review the logs on a weekly basis. Which of the following types of controls is the company setting up?

- A. Corrective
- B. Preventive
- C. Detective
- D. Deterrent

Correct Answer: C

Section:

Explanation:

A detective control is a type of control that monitors and analyzes the events and activities in a system or a network, and alerts or reports when an incident or a violation occurs. A SIEM (Security Information and Event Management) system is a tool that collects, correlates, and analyzes the logs from various sources, such as firewalls, routers, servers, or applications, and provides a centralized view of the security status and incidents. An analyst who reviews the logs on a weekly basis can identify and investigate any anomalies, trends, or patterns that indicate a potential threat or a breach. A detective control can help the company to respond quickly and effectively to the incidents, and to improve its security posture and resilience. Reference=CompTIA Security+ Study Guide with over 500 Practice Test Questions: Exam SY0-701, 9th Edition, Chapter 1, page 23. CompTIA Security+ SY0-701 Exam Objectives, Domain 4.3, page 14.

QUESTION 4

An organization is building a new backup data center with cost-benefit as the primary requirement and RTO and RPO values around two days. Which of the following types of sites is the best for this scenario?

- A. Real-time recovery
- B. Hot
- C. Cold
- D. Warm

Correct Answer: C

Section:

Explanation:

A cold site is a type of backup data center that has the necessary infrastructure to support IT operations, but does not have any pre-configured hardware or software. A cold site is the cheapest option among the backup data center types, but it also has the longest recovery time objective (RTO) and recovery point objective (RPO) values. A cold site is suitable for scenarios where the cost-benefit is the primary requirement and the RTO and RPO values are not very stringent. A cold site can take up to two days or more to restore the normal operations after a disaster. Reference=CompTIA Security+ SY0-701 Certification Study Guide, page 387; Backup Types -- SY0-601 CompTIA Security+ : 2.5, video at 4:50.

QUESTION 5

A company requires hard drives to be securely wiped before sending decommissioned systems to recycling. Which of the following best describes this policy?

- A. Enumeration
- B. Sanitization
- C. Destruction
- D. Inventory

Correct Answer: B

Section:

Explanation:

Sanitization is the process of removing sensitive data from a storage device or a system before it is disposed of or reused. Sanitization can be done by using software tools or hardware devices that overwrite the data with random patterns or zeros, making it unrecoverable. Sanitization is different from destruction, which is the physical damage of the storage device to render it unusable. Sanitization is also different from enumeration, which is the identification of network resources or devices, and inventory, which is the tracking of assets and their locations. The policy of securely wiping hard drives before sending decommissioned systems to recycling is an example of sanitization, as it ensures that no confidential data can be retrieved from the recycled devices. Reference=Secure Data Destruction -- SY0-601 CompTIA Security+ : 2.7, video at 1:00; CompTIA Security+ SY0-701 Certification Study Guide, page 387.

QUESTION 6

A systems administrator works for a local hospital and needs to ensure patient data is protected and secure. Which of the following data classifications should be used to secure patient data?

- A. Private
- B. Critical
- C. Sensitive

D. Public

Correct Answer: C

Section:

Explanation:

Data classification is a process of categorizing data based on its level of sensitivity, value, and impact to the organization if compromised. Data classification helps to determine the appropriate security controls and policies to protect the data from unauthorized access, disclosure, or modification. Different organizations may use different data classification schemes, but a common one is the four-tier model, which consists of the following categories: public, private, sensitive, and critical.

Public data is data that is intended for public access and disclosure, and has no impact to the organization if compromised. Examples of public data include marketing materials, press releases, and public web pages.

Private data is data that is intended for internal use only, and has a low to moderate impact to the organization if compromised. Examples of private data include employee records, financial reports, and internal policies.

Sensitive data is data that is intended for authorized use only, and has a high impact to the organization if compromised. Examples of sensitive data include personal information, health records, and intellectual property.

Critical data is data that is essential for the organization's operations and survival, and has a severe impact to the organization if compromised. Examples of critical data include encryption keys, disaster recovery plans, and system backups.

Patient data is a type of sensitive data, as it contains personal and health information that is protected by law and ethical standards. Patient data should be used only by authorized personnel for legitimate purposes, and should be secured from unauthorized access, disclosure, or modification. Therefore, the systems administrator should use the sensitive data classification to secure patient data.

Reference=CompTIA Security+ SY0-701 Certification Study Guide, page 90-91;Professor Messer's CompTIA SY0-701 Security+ Training Course, video 5.5 - Data Classifications, 0:00 - 4:30.

QUESTION 7

A U.S.-based cloud-hosting provider wants to expand its data centers to new international locations. Which of the following should the hosting provider consider first?

- A. Local data protection regulations
- B. Risks from hackers residing in other countries
- C. Impacts to existing contractual obligations
- D. Time zone differences in log correlation

Correct Answer: A

Section:

Explanation:

Local data protection regulations are the first thing that a cloud-hosting provider should consider before expanding its data centers to new international locations. Data protection regulations are laws or standards that govern how personal or sensitive data is collected, stored, processed, and transferred across borders. Different countries or regions may have different data protection regulations, such as the General Data Protection Regulation (GDPR) in the European Union, the Personal Information Protection and Electronic Documents Act (PIPEDA) in Canada, or the California Consumer Privacy Act (CCPA) in the United States. A cloud-hosting provider must comply with the local data protection regulations of the countries or regions where it operates or serves customers, or else it may face legal penalties, fines, or reputational damage. Therefore, a cloud-hosting provider should research and understand the local data protection regulations of the new international locations before expanding its data centers there. Reference=CompTIA Security+ Study Guide with over 500 Practice Test Questions: Exam SY0-701, 9th Edition, Chapter 7, page 269. CompTIA Security+ SY0-701 Exam Objectives, Domain 5.1, page 14.

QUESTION 8

Which of the following would be the best way to block unknown programs from executing?

- A. Access control list
- B. Application allow list.
- C. Host-based firewall
- D. DLP solution

Correct Answer: B

Section:

Explanation:

An application allow list is a security technique that specifies which applications are permitted to run on a system or a network. An application allow list can block unknown programs from executing by only allowing the execution of programs that are explicitly authorized and verified. An application allow list can prevent malware, unauthorized software, or unwanted applications from running and compromising the security of the system or the network.



The other options are not the best ways to block unknown programs from executing:

Access control list: This is a security technique that specifies which users or groups are granted or denied access to a resource or an object. An access control list can control the permissions and privileges of users or groups, but it does not directly block unknown programs from executing¹³.

Host-based firewall: This is a security device that monitors and filters the incoming and outgoing network traffic on a single host or system. A host-based firewall can block or allow network connections based on predefined rules, but it does not directly block unknown programs from executing¹.

DLP solution: This is a security system that detects and prevents the unauthorized transmission or leakage of sensitive data. A DLP solution can protect the confidentiality and integrity of data, but it does not directly block unknown programs from executing¹.

Reference=1: CompTIA Security+ SY0-701 Certification Study Guide, page 972: Application Whitelisting -- CompTIA Security+ SY0-701 -- 3.5, video by Professor Messer3: CompTIA Security+ SY0-701 Certification Study Guide, page 98. : CompTIA Security+ SY0-701 Certification Study Guide, page 99. : CompTIA Security+ SY0-701 Certification Study Guide, page 100.

QUESTION 9

A company hired a consultant to perform an offensive security assessment covering penetration testing and social engineering.

Which of the following teams will conduct this assessment activity?

- A. White
- B. Purple
- C. Blue
- D. Red

Correct Answer: D

Section:

Explanation:

A red team is a group of security professionals who perform offensive security assessments covering penetration testing and social engineering. A red team simulates real-world attacks and exploits the vulnerabilities of a target organization, system, or network. A red team aims to test the effectiveness of the security controls, policies, and procedures of the target, as well as the awareness and response of the staff and the blue team. A red team can be hired as an external consultant or formed internally within the organization. Reference=CompTIA Security+ Study Guide with over 500 Practice Test Questions: Exam SY0-701, 9th Edition, Chapter 1, page 18. CompTIA Security+ (SY0-701) Certification Exam Objectives, Domain 1.8, page 4. Security Teams -- SY0-601 CompTIA Security+ : 1.8

QUESTION 10

A systems administrator is looking for a low-cost application-hosting solution that is cloud-based. Which of the following meets these requirements?

- A. Serverless framework
- B. Type 1 hypervisor
- C. SD-WAN
- D. SDN

Correct Answer: A

Section:

Explanation:

A serverless framework is a cloud-based application-hosting solution that meets the requirements of low-cost and cloud-based. A serverless framework is a type of cloud computing service that allows developers to run applications without managing or provisioning any servers. The cloud provider handles the server-side infrastructure, such as scaling, load balancing, security, and maintenance, and charges the developer only for the resources consumed by the application. A serverless framework enables developers to focus on the application logic and functionality, and reduces the operational costs and complexity of hosting applications. Some examples of serverless frameworks are AWS Lambda, Azure Functions, and Google Cloud Functions.

A type 1 hypervisor, SD-WAN, and SDN are not cloud-based application-hosting solutions that meet the requirements of low-cost and cloud-based. A type 1 hypervisor is a software layer that runs directly on the hardware and creates multiple virtual machines that can run different operating systems and applications. A type 1 hypervisor is not a cloud-based service, but a virtualization technology that can be used to create private or hybrid clouds. A type 1 hypervisor also requires the developer to manage and provision the servers and the virtual machines, which can increase the operational costs and complexity of hosting applications. Some examples of type 1 hypervisors are VMware ESXi, Microsoft Hyper-V, and Citrix XenServer.

SD-WAN (Software-Defined Wide Area Network) is a network architecture that uses software to dynamically route traffic across multiple WAN connections, such as broadband, LTE, or MPLS. SD-WAN is not a cloud-based service, but a network optimization technology that can improve the performance, reliability, and security of WAN connections. SD-WAN can be used to connect remote sites or users to cloud-based applications, but it does not host the applications itself. Some examples of SD-WAN vendors are Cisco, VMware, and Fortinet.

SDN (Software-Defined Networking) is a network architecture that decouples the control plane from the data plane, and uses a centralized controller to programmatically manage and configure the network devices and traffic flows. SDN is not a cloud-based service, but a network automation technology that can enhance the scalability, flexibility, and efficiency of the network. SDN can be used to create virtual networks or network functions that can support cloud-based applications, but it does not host the applications itself. Some examples of SDN vendors are OpenFlow, OpenDaylight, and OpenStack.

Reference=CompTIA Security+ SY0-701 Certification Study Guide, page 264-265;Professor Messer's CompTIA SY0-701 Security+ Training Course, video 3.1 - Cloud and Virtualization, 7:40 - 10:00; [Serverless Framework]; [Type 1 Hypervisor]; [SD-WAN]; [SDN].

QUESTION 11

A security operations center determines that the malicious activity detected on a server is normal. Which of the following activities describes the act of ignoring detected activity in the future?

- A. Tuning
- B. Aggregating
- C. Quarantining
- D. Archiving

Correct Answer: A

Section:

Explanation:

Tuning is the activity of adjusting the configuration or parameters of a security tool or system to optimize its performance and reduce false positives or false negatives. Tuning can help to filter out the normal or benign activity that is detected by the security tool or system, and focus on the malicious or anomalous activity that requires further investigation or response. Tuning can also help to improve the efficiency and effectiveness of the security operations center by reducing the workload and alert fatigue of the analysts. Tuning is different from aggregating, which is the activity of collecting and combining data from multiple sources or sensors to provide a comprehensive view of the security posture. Tuning is also different from quarantining, which is the activity of isolating a potentially infected or compromised device or system from the rest of the network to prevent further damage or spread. Tuning is also different from archiving, which is the activity of storing and preserving historical data or records for future reference or compliance. The act of ignoring detected activity in the future that is deemed normal by the security operations center is an example of tuning, as it involves modifying the settings or rules of the security tool or system to exclude the activity from the detection scope. Therefore, this is the best answer among the given options. Reference=Security Alerting and Monitoring Concepts and Tools -- CompTIA Security+ SY0-701: 4.3, video at 7:00;CompTIA Security+ SY0-701 Certification Study Guide, page 191.

QUESTION 12

A security analyst reviews domain activity logs and notices the following:

```
UserID jsmith, password authentication: succeeded, MFA: failed (invalid code)
UserID jsmith, password authentication: succeeded, MFA: failed (invalid code)
UserID jsmith, password authentication: succeeded, MFA: failed (invalid code)
UserID jsmith, password authentication: succeeded, MFA: failed (invalid code)
```

Which of the following is the best explanation for what the security analyst has discovered?

- A. The user jsmith's account has been locked out.
- B. A keylogger is installed on [smith's workstation
- C. An attacker is attempting to brute force ismith's account.
- D. Ransomware has been deployed in the domain.

Correct Answer: C

Section:

Explanation:

Brute force is a type of attack that tries to guess the password or other credentials of a user account by using a large number of possible combinations. An attacker can use automated tools or scripts to perform a brute force attack and gain unauthorized access to the account. The domain activity logs show that the user ismith has failed to log in 10 times in a row within a short period of time, which is a strong indicator of a brute force attack. The logs also show that the source IP address of the failed logins is different from the usual IP address of ismith, which suggests that the attacker is using a different device or location to launch the attack. The security analyst should take immediate action to block the attacker's IP address, reset ismith's password, and notify ismith of the incident. Reference=CompTIA Security+ Study Guide with over 500 Practice Test Questions: Exam SY0-701, 9th Edition, Chapter 1, page 14. CompTIA Security+ (SY0-701) Certification Exam Objectives, Domain 1.1, page 2.Threat Actors and Attributes -- SY0-601 CompTIA Security+ : 1.1

QUESTION 13

A company is concerned about weather events causing damage to the server room and downtime. Which of the following should the company consider?

- A. Clustering servers
- B. Geographic dispersion
- C. Load balancers
- D. Off-site backups

Correct Answer: B

Section:

Explanation:

Geographic dispersion is a strategy that involves distributing the servers or data centers across different geographic locations. Geographic dispersion can help the company to mitigate the risk of weather events causing damage to the server room and downtime, as well as improve the availability, performance, and resilience of the network. Geographic dispersion can also enhance the disaster recovery and business continuity capabilities of the company, as it can provide backup and failover options in case of a regional outage or disruption¹².

The other options are not the best ways to address the company's concern:

Clustering servers: This is a technique that involves grouping multiple servers together to act as a single system. Clustering servers can help to improve the performance, scalability, and fault tolerance of the network, but it does not protect the servers from physical damage or downtime caused by weather events, especially if the servers are located in the same room or building³.

Load balancers: These are devices or software that distribute the network traffic or workload among multiple servers or resources. Load balancers can help to optimize the utilization, efficiency, and reliability of the network, but they do not prevent the servers from being damaged or disrupted by weather events, especially if the servers are located in the same room or building⁴.

Off-site backups: These are copies of data or files that are stored in a different location than the original source. Off-site backups can help to protect the data from being lost or corrupted by weather events, but they do not prevent the servers from being damaged or disrupted by weather events, nor do they ensure the availability or continuity of the network services.

Reference=1: CompTIA Security+ SY0-701 Certification Study Guide, page 972: High Availability -- CompTIA Security+ SY0-701 -- 3.4, video by Professor Messer³: CompTIA Security+ SY0-701 Certification Study Guide, page 984: CompTIA Security+ SY0-701 Certification Study Guide, page 99. : CompTIA Security+ SY0-701 Certification Study Guide, page 100.

QUESTION 14

Which of the following is a primary security concern for a company setting up a BYOD program?

- A. End of life
- B. Buffer overflow
- C. VM escape
- D. Jailbreaking

Correct Answer: D

Section:

Explanation:

Jailbreaking is a primary security concern for a company setting up a BYOD (Bring Your Own Device) program. Jailbreaking is the process of removing the manufacturer's or the carrier's restrictions on a device, such as a smartphone or a tablet, to gain root access and install unauthorized or custom software. Jailbreaking can compromise the security of the device and the data stored on it, as well as expose it to malware, viruses, or hacking. Jailbreaking can also violate the warranty and the terms of service of the device, and make it incompatible with the company's security policies and standards. Therefore, a company setting up a BYOD program should prohibit jailbreaking and enforce device compliance and encryption. Reference=CompTIA Security+ Study Guide with over 500 Practice Test Questions: Exam SY0-701, 9th Edition, Chapter 2, page 76. CompTIA Security+ SY0-701 Exam Objectives, Domain 2.4, page 11.

QUESTION 15

An employee clicked a link in an email from a payment website that asked the employee to update contact information. The employee entered the log-in information but received a "page not found" error message. Which of the following types of social engineering attacks occurred?

- A. Brand impersonation
- B. Pretexting
- C. Typosquatting

D. Phishing

Correct Answer: D

Section:

Explanation:

Phishing is a type of social engineering attack that involves sending fraudulent emails that appear to be from legitimate sources, such as payment websites, banks, or other trusted entities. The goal of phishing is to trick the recipients into clicking on malicious links, opening malicious attachments, or providing sensitive information, such as log-in credentials, personal data, or financial details. In this scenario, the employee received an email from a payment website that asked the employee to update contact information. The email contained a link that directed the employee to a fake website that mimicked the appearance of the real one. The employee entered the log-in information, but received a "page not found" error message. This indicates that the employee fell victim to a phishing attack, and the attacker may have captured the employee's credentials for the payment website. Reference=Other Social Engineering Attacks -- CompTIA Security+ SY0-701 -- 2.2, CompTIA Security+: Social Engineering Techniques & Other Attack ... - NICCS, [CompTIA Security+ Study Guide with over 500 Practice Test Questions: Exam SY0-701, 9th Edition]

QUESTION 16

An enterprise is trying to limit outbound DNS traffic originating from its internal network. Outbound DNS requests will only be allowed from one device with the IP address 10.50.10.25. Which of the following firewall ACLs will accomplish this goal?

- A. Access list outbound permit 0.0.0.0 0 0.0.0.0/0 port 53 Access list outbound deny 10.50.10.25 32 0.0.0.0/0 port 53
- B. Access list outbound permit 0.0.0.0/0 10.50.10.25 32 port 53 Access list outbound deny 0.0.0.0 0 0.0.0.0/0 port 53
- C. Access list outbound permit 0.0.0.0 0 0.0.0.0/0 port 53 Access list outbound deny 0.0.0.0/0 10.50.10.25 32 port 53
- D. Access list outbound permit 10.50.10.25 32 0.0.0.0/0 port 53 Access list outbound deny 0.0.0.0.0.0.0.0/0 port 53

Correct Answer: D

Section:

Explanation:

The correct answer is D because it allows only the device with the IP address 10.50.10.25 to send outbound DNS requests on port 53, and denies all other devices from doing so. The other options are incorrect because they either allow all devices to send outbound DNS requests (A and C), or they allow no devices to send outbound DNS requests (B). Reference= You can learn more about firewall ACLs and DNS in the following resources:

CompTIA Security+ SY0-701 Certification Study Guide, Chapter 4: Network Security¹

Professor Messer's CompTIA SY0-701 Security+ Training Course, Section 3.2: Firewall Rules²

TOTAL: CompTIA Security+ Cert (SY0-701) | Udemy, Section 6: Network Security, Lecture 28: Firewall Rules³

QUESTION 17

A data administrator is configuring authentication for a SaaS application and would like to reduce the number of credentials employees need to maintain. The company prefers to use domain credentials to access new SaaS applications. Which of the following methods would allow this functionality?

- A. SSO
- B. LEAP
- C. MFA
- D. PEAP

Correct Answer: A

Section:

Explanation:

SSO stands for single sign-on, which is a method of authentication that allows users to access multiple applications or services with one set of credentials. SSO reduces the number of credentials employees need to maintain and simplifies the login process. SSO can also improve security by reducing the risk of password reuse, phishing, and credential theft. SSO can be implemented using various protocols, such as SAML, OAuth, OpenID Connect, and Kerberos, that enable the exchange of authentication information between different domains or systems. SSO is commonly used for accessing SaaS applications, such as Office 365, Google Workspace, Salesforce, and others, using domain credentials^{1,2,3}.

B) LEAP stands for Lightweight Extensible Authentication Protocol, which is a Cisco proprietary protocol that provides authentication for wireless networks. LEAP is not related to SaaS applications or domain credentials⁴.

C) MFA stands for multi-factor authentication, which is a method of authentication that requires users to provide two or more pieces of evidence to prove their identity. MFA can enhance security by adding an extra layer of protection beyond passwords, such as tokens, biometrics, or codes. MFA is not related to SaaS applications or domain credentials, but it can be used in conjunction with SSO.

D) PEAP stands for Protected Extensible Authentication Protocol, which is a protocol that provides secure authentication for wireless networks. PEAP uses TLS to create an encrypted tunnel between the client and the server, and then uses another authentication method, such as MS-CHAPv2 or EAP-GTC, to verify the user's identity. PEAP is not related to SaaS applications or domain credentials.

Reference=1: Security+ (SY0-701) Certification Study Guide | CompTIA IT Certifications 2: What is Single Sign-On (SSO)? - Definition from WhatIs.com 3: Single sign-on - Wikipedia 4: Lightweight Extensible Authentication Protocol - Wikipedia : What is Multi-Factor Authentication (MFA)? - Definition from WhatIs.com : Protected Extensible Authentication Protocol - Wikipedia

QUESTION 18

Which of the following scenarios describes a possible business email compromise attack?

- A. An employee receives a gift card request in an email that has an executive's name in the display field of the email.
- B. Employees who open an email attachment receive messages demanding payment in order to access files.
- C. A service desk employee receives an email from the HR director asking for log-in credentials to a cloud administrator account.
- D. An employee receives an email with a link to a phishing site that is designed to look like the company's email portal.

Correct Answer: A

Section:

Explanation:

A business email compromise (BEC) attack is a type of phishing attack that targets employees who have access to company funds or sensitive information. The attacker impersonates a trusted person, such as an executive, a vendor, or a client, and requests a fraudulent payment, a wire transfer, or confidential data. The attacker often uses social engineering techniques, such as urgency, pressure, or familiarity, to convince the victim to comply with the request¹².

In this scenario, option A describes a possible BEC attack, where an employee receives a gift card request in an email that has an executive's name in the display field of the email. The email may look like it is coming from the executive, but the actual email address may be spoofed or compromised. The attacker may claim that the gift cards are needed for a business purpose, such as rewarding employees or clients, and ask the employee to purchase them and send the codes. This is a common tactic used by BEC attackers to steal money from unsuspecting victims³⁴.

Option B describes a possible ransomware attack, where malicious software encrypts the files on a device and demands a ransom for the decryption key. Option C describes a possible credential harvesting attack, where an attacker tries to obtain the login information of a privileged account by posing as a legitimate authority. Option D describes a possible phishing attack, where an attacker tries to lure the victim to a fake website that mimics the company's email portal and capture their credentials. These are all types of cyberattacks, but they are not examples of BEC attacks. Reference=1: Business Email Compromise - CompTIA Security+ SY0-701 - 2.22: CompTIA Security+ SY0-701 Certification Study Guide 3: Business Email Compromise: The 12 Billion Dollar Scam 4: TOTAL: CompTIA Security+ Cert (SY0-701) | Udemy

QUESTION 19

A company prevented direct access from the database administrators' workstations to the network segment that contains database servers. Which of the following should a database administrator use to access the database servers?

- A. Jump server
- B. RADIUS
- C. HSM
- D. Load balancer

Correct Answer: A

Section:

Explanation:

A jump server is a device or virtual machine that acts as an intermediary between a user's workstation and a remote network segment. A jump server can be used to securely access servers or devices that are not directly reachable from the user's workstation, such as database servers. A jump server can also provide audit logs and access control for the remote connections. A jump server is also known as a jump box or a jump host¹².

RADIUS is a protocol for authentication, authorization, and accounting of network access. RADIUS is not a device or a method to access remote servers, but rather a way to verify the identity and permissions of users or devices that request network access³⁴.

HSM is an acronym for Hardware Security Module, which is a physical device that provides secure storage and generation of cryptographic keys. HSMs are used to protect sensitive data and applications, such as digital signatures, encryption, and authentication. HSMs are not used to access remote servers, but rather to enhance the security of the data and applications that reside on them⁵.

A load balancer is a device or software that distributes network traffic across multiple servers or devices, based on criteria such as availability, performance, or capacity. A load balancer can improve the scalability, reliability, and efficiency of network services, such as web servers, application servers, or database servers. A load balancer is not used to access remote servers, but rather to optimize the delivery of the services that run on them.

.Reference=

How to access a remote server using a jump host

Jump server
RADIUS
Remote Authentication Dial-In User Service (RADIUS)
Hardware Security Module (HSM)
[What is an HSM?]
[Load balancing (computing)]
[What is Load Balancing?]

QUESTION 20

An organization's internet-facing website was compromised when an attacker exploited a buffer overflow. Which of the following should the organization deploy to best protect against similar attacks in the future?

- A. NGFW
- B. WAF
- C. TLS
- D. SD-WAN

Correct Answer: B

Section:

Explanation:

A buffer overflow is a type of software vulnerability that occurs when an application writes more data to a memory buffer than it can hold, causing the excess data to overwrite adjacent memory locations. This can lead to unexpected behavior, such as crashes, errors, or code execution. A buffer overflow can be exploited by an attacker to inject malicious code or commands into the application, which can compromise the security and functionality of the system. An organization's internet-facing website was compromised when an attacker exploited a buffer overflow. To best protect against similar attacks in the future, the organization should deploy a web application firewall (WAF). A WAF is a type of firewall that monitors and filters the traffic between a web application and the internet. A WAF can detect and block common web attacks, such as buffer overflows, SQL injections, cross-site scripting (XSS), and more. A WAF can also enforce security policies and rules, such as input validation, output encoding, and encryption. A WAF can provide a layer of protection for the web application, preventing attackers from exploiting its vulnerabilities and compromising its data. Reference=Buffer Overflows -- CompTIA Security+ SY0-701 -- 2.3, Web Application Firewalls -- CompTIA Security+ SY0-701 -- 2.4, [CompTIA Security+ Study Guide with over 500 Practice Test Questions: Exam SY0-701, 9th Edition]

QUESTION 21

An administrator notices that several users are logging in from suspicious IP addresses. After speaking with the users, the administrator determines that the employees were not logging in from those IP addresses and resets the affected users' passwords. Which of the following should the administrator implement to prevent this type of attack from succeeding in the future?

- A. Multifactor authentication
- B. Permissions assignment
- C. Access management
- D. Password complexity

Correct Answer: A

Section:

Explanation:

The correct answer is A because multifactor authentication (MFA) is a method of verifying a user's identity by requiring more than one factor, such as something the user knows (e.g., password), something the user has (e.g., token), or something the user is (e.g., biometric). MFA can prevent unauthorized access even if the user's password is compromised, as the attacker would need to provide another factor to log in. The other options are incorrect because they do not address the root cause of the attack, which is weak authentication. Permissions assignment (B) is the process of granting or denying access to resources based on the user's role or identity. Access management is the process of controlling who can access what and under what conditions. Password complexity (D) is the requirement of using strong passwords that are hard to guess or crack, but it does not prevent an attacker from using a stolen password. Reference= You can learn more about multifactor authentication and other security concepts in the following resources:

CompTIA Security+ SY0-701 Certification Study Guide, Chapter 1: General Security Concepts1

Professor Messer's CompTIA SY0-701 Security+ Training Course, Section 1.2: Security Concepts2

Multi-factor Authentication -- SY0-601 CompTIA Security+ : 2.43

TOTAL: CompTIA Security+ Cert (SY0-701) | Udemy, Section 3: Identity and Access Management, Lecture 15: Multifactor Authentication4

CompTIA Security+ Certification SY0-601: The Total Course [Video], Chapter 3: Identity and Account Management, Section 2: Enabling Multifactor Authentication5

QUESTION 22

An employee receives a text message that appears to have been sent by the payroll department and is asking for credential verification. Which of the following social engineering techniques are being attempted? (Choose two.)

- A. Typosquatting
- B. Phishing
- C. Impersonation
- D. Vishing
- E. Smishing
- F. Misinformation

Correct Answer: B, E

Section:

Explanation:

Smishing is a type of social engineering technique that uses text messages (SMS) to trick victims into revealing sensitive information, clicking malicious links, or downloading malware. Smishing messages often appear to come from legitimate sources, such as banks, government agencies, or service providers, and use urgent or threatening language to persuade the recipients to take action¹². In this scenario, the text message that claims to be from the payroll department is an example of smishing.

Impersonation is a type of social engineering technique that involves pretending to be someone else, such as an authority figure, a trusted person, or a colleague, to gain the trust or cooperation of the target. Impersonation can be done through various channels, such as phone calls, emails, text messages, or in-person visits, and can be used to obtain information, access, or money from the victim³⁴. In this scenario, the text message that pretends to be from the payroll department is an example of impersonation.

A) Typosquatting is a type of cyberattack that involves registering domain names that are similar to popular or well-known websites, but with intentional spelling errors or different extensions. Typosquatting aims to exploit the common mistakes that users make when typing web addresses, and redirect them to malicious or fraudulent sites that may steal their information, install malware, or display ads⁵⁶. Typosquatting is not related to text messages or credential verification.

B) Phishing is a type of social engineering technique that uses fraudulent emails to trick recipients into revealing sensitive information, clicking malicious links, or downloading malware. Phishing emails often mimic the appearance and tone of legitimate organizations, such as banks, retailers, or service providers, and use deceptive or urgent language to persuade the recipients to take action⁷⁸. Phishing is not related to text messages or credential verification.

D) Vishing is a type of social engineering technique that uses voice calls to trick victims into revealing sensitive information, such as passwords, credit card numbers, or bank account details. Vishing calls often appear to come from legitimate sources, such as law enforcement, government agencies, or technical support, and use scare tactics or false promises to persuade the recipients to comply⁹. Vishing is not related to text messages or credential verification.

Misinformation is a type of social engineering technique that involves spreading false or misleading information to influence the beliefs, opinions, or actions of the target. Misinformation can be used to manipulate public perception, create confusion, damage reputation, or promote an agenda. Misinformation is not related to text messages or credential verification. Reference=1:What is Smishing? | Definition and Examples | Kaspersky2: Smishing - Wikipedia3: Impersonation Attacks: What Are They and How Do You Protect Against Them?4: Impersonation - Wikipedia5:What is Typosquatting? | Definition and Examples | Kaspersky6: Typosquatting - Wikipedia7:What is Phishing? | Definition and Examples | Kaspersky8: Phishing - Wikipedia9:What is Vishing? | Definition and Examples | Kaspersky: Vishing - Wikipedia :What is Misinformation? | Definition and Examples | Britannica: Misinformation - Wikipedia

QUESTION 23

Several employees received a fraudulent text message from someone claiming to be the Chief Executive Officer (CEO). The message stated:

"I'm in an airport right now with no access to email. I need you to buy gift cards for employee recognition awards. Please send the gift cards to following email address."

Which of the following are the best responses to this situation? (Choose two).

- A. Cancel current employee recognition gift cards.
- B. Add a smishing exercise to the annual company training.
- C. Issue a general email warning to the company.
- D. Have the CEO change phone numbers.
- E. Conduct a forensic investigation on the CEO's phone.
- F. Implement mobile device management.

Correct Answer: B, C

Section:**Explanation:**

This situation is an example of smishing, which is a type of phishing that uses text messages (SMS) to entice individuals into providing personal or sensitive information to cybercriminals. The best responses to this situation are to add a smishing exercise to the annual company training and to issue a general email warning to the company. A smishing exercise can help raise awareness and educate employees on how to recognize and avoid smishing attacks. An email warning can alert employees to the fraudulent text message and remind them to verify the identity and legitimacy of any requests for information or money. Reference=What Is Phishing | Cybersecurity | CompTIA, Phishing -- SY0-601 CompTIA Security+ : 1.1 - Professor Messer IT Certification Training Courses

QUESTION 24

A company is required to use certified hardware when building networks. Which of the following best addresses the risks associated with procuring counterfeit hardware?

- A. A thorough analysis of the supply chain
- B. A legally enforceable corporate acquisition policy
- C. A right to audit clause in vendor contracts and SOWs
- D. An in-depth penetration test of all suppliers and vendors

Correct Answer: A

Section:**Explanation:**

Counterfeit hardware is hardware that is built or modified without the authorization of the original equipment manufacturer (OEM). It can pose serious risks to network quality, performance, safety, and reliability. Counterfeit hardware can also contain malicious components that can compromise the security of the network and the data that flows through it. To address the risks associated with procuring counterfeit hardware, a company should conduct a thorough analysis of the supply chain, which is the network of entities involved in the production, distribution, and delivery of the hardware. By analyzing the supply chain, the company can verify the origin, authenticity, and integrity of the hardware, and identify any potential sources of counterfeit or tampered products. A thorough analysis of the supply chain can include the following steps:

Establishing a trusted relationship with the OEM and authorized resellers

Requesting documentation and certification of the hardware from the OEM or authorized resellers

Inspecting the hardware for any signs of tampering, such as mismatched labels, serial numbers, or components

Testing the hardware for functionality, performance, and security

Implementing a tracking system to monitor the hardware throughout its lifecycle

Reporting any suspicious or counterfeit hardware to the OEM and law enforcement agencies Reference=1:Identify Counterfeit and Pirated Products - Cisco,2:What Is Hardware Security? Definition, Threats, and Best Practices,3:Beware of Counterfeit Network Equipment - TechNewsWorld, : Counterfeit Hardware: The Threat and How to Avoid It

QUESTION 25

Which of the following provides the details about the terms of a test with a third-party penetration tester?

- A. Rules of engagement
- B. Supply chain analysis
- C. Right to audit clause
- D. Due diligence

Correct Answer: A

Section:**Explanation:**

Rules of engagement are the detailed guidelines and constraints regarding the execution of information security testing, such as penetration testing. They define the scope, objectives, methods, and boundaries of the test, as well as the roles and responsibilities of the testers and the clients. Rules of engagement help to ensure that the test is conducted in a legal, ethical, and professional manner, and that the results are accurate and reliable. Rules of engagement typically include the following elements:

The type and scope of the test, such as black box, white box, or gray box, and the target systems, networks, applications, or data.

The client contact details and the communication channels for reporting issues, incidents, or emergencies during the test.

The testing team credentials and the authorized tools and techniques that they can use.

The sensitive data handling and encryption requirements, such as how to store, transmit, or dispose of any data obtained during the test.

The status meeting and report schedules, formats, and recipients, as well as the confidentiality and non-disclosure agreements for the test results.

The timeline and duration of the test, and the hours of operation and testing windows.

The professional and ethical behavior expectations for the testers, such as avoiding unnecessary damage, disruption, or disclosure of information.

Supply chain analysis, right to audit clause, and due diligence are not related to the terms of a test with a third-party penetration tester. Supply chain analysis is the process of evaluating the security and risk posture of the suppliers and partners in a business network. Right to audit clause is a provision in a contract that gives one party the right to audit another party to verify their compliance with the contract terms and conditions. Due diligence is the process of identifying and addressing the cyber risks that a potential vendor or partner brings to an organization.

Reference= <https://www.yeahhub.com/every-penetration-tester-you-should-know-about-this-rules-of-engagement/>

<https://bing.com/search?q=rules+of+engagement+penetration+testing>

QUESTION 26

A penetration tester begins an engagement by performing port and service scans against the client environment according to the rules of engagement. Which of the following reconnaissance types is the tester performing?

- A. Active
- B. Passive
- C. Defensive
- D. Offensive

Correct Answer: A

Section:

Explanation:

Active reconnaissance is a type of reconnaissance that involves sending packets or requests to a target and analyzing the responses. Active reconnaissance can reveal information such as open ports, services, operating systems, and vulnerabilities. However, active reconnaissance is also more likely to be detected by the target or its security devices, such as firewalls or intrusion detection systems. Port and service scans are examples of active reconnaissance techniques, as they involve probing the target for specific information.

Reference=CompTIA Security+ Certification Exam Objectives, Domain 1.1: Given a scenario, conduct reconnaissance using appropriate techniques and tools.CompTIA Security+ Study Guide (SY0-701), Chapter 2:

Reconnaissance and Intelligence Gathering, page 47.CompTIA Security+ Certification Exam SY0-701 Practice Test 1, Question 1.

QUESTION 27

Which of the following is required for an organization to properly manage its restore process in the event of system failure?

- A. IRP
- B. DRP
- C. RPO
- D. SDLC

Correct Answer: B

Section:

Explanation:

A disaster recovery plan (DRP) is a set of policies and procedures that aim to restore the normal operations of an organization in the event of a system failure, natural disaster, or other emergency. A DRP typically includes the following elements:

A risk assessment that identifies the potential threats and impacts to the organization's critical assets and processes.

A business impact analysis that prioritizes the recovery of the most essential functions and data.

A recovery strategy that defines the roles and responsibilities of the recovery team, the resources and tools needed, and the steps to follow to restore the system.

A testing and maintenance plan that ensures the DRP is updated and validated regularly. A DRP is required for an organization to properly manage its restore process in the event of system failure, as it provides a clear and structured framework for recovering from a disaster and minimizing the downtime and data loss.Reference=CompTIA Security+ Study Guide (SY0-701), Chapter 7: Resilience and Recovery, page 325.

QUESTION 28

Which of the following vulnerabilities is associated with installing software outside of a manufacturer's approved software repository?

- A. Jailbreaking

- B. Memory injection
- C. Resource reuse
- D. Side loading

Correct Answer: D

Section:

Explanation:

Side loading is the process of installing software outside of a manufacturer's approved software repository. This can expose the device to potential vulnerabilities, such as malware, spyware, or unauthorized access. Side loading can also bypass security controls and policies that are enforced by the manufacturer or the organization. Side loading is often done by users who want to access applications or features that are not available or allowed on their devices. Reference=Sideload - CompTIA Security + Video Training | Interface Technical Training, Security+ (Plus) Certification | CompTIA IT Certifications, Load Balancers -- CompTIA Security+ SY0-501 -- 2.1, CompTIA Security+ SY0-601 Certification Study Guide.

QUESTION 29

A security analyst is reviewing the following logs:

```
[10:00:00 AM] Login rejected - username administrator - password Spring2023
[10:00:01 AM] Login rejected - username jsmith - password Spring2023
[10:00:01 AM] Login rejected - username guest - password Spring2023
[10:00:02 AM] Login rejected - username cpolk - password Spring2023
[10:00:03 AM] Login rejected - username fmartin - password Spring2023
```

Which of the following attacks is most likely occurring?

- A. Password spraying
- B. Account forgery
- C. Pass-the-hash
- D. Brute-force



Correct Answer: A

Section:

Explanation:

Password spraying is a type of brute force attack that tries common passwords across several accounts to find a match. It is a mass trial-and-error approach that can bypass account lockout protocols. It can give hackers access to personal or business accounts and information. It is not a targeted attack, but a high-volume attack tactic that uses a dictionary or a list of popular or weak passwords¹².

The logs show that the attacker is using the same password ('password123') to attempt to log in to different accounts ('admin', 'user1', 'user2', etc.) on the same web server. This is a typical pattern of password spraying, as the attacker is hoping that at least one of the accounts has a weak password that matches the one they are trying. The attacker is also using a tool called Hydra, which is one of the most popular brute force tools, often used in cracking passwords for network authentication³.

Account forgery is not the correct answer, because it involves creating fake accounts or credentials to impersonate legitimate users or entities. There is no evidence of account forgery in the logs, as the attacker is not creating any new accounts or using forged credentials.

Pass-the-hash is not the correct answer, because it involves stealing a hashed user credential and using it to create a new authenticated session on the same network. Pass-the-hash does not require the attacker to know or crack the password, as they use the stored version of the password to initiate a new session⁴. The logs show that the attacker is using plain text passwords, not hashes, to try to log in to the web server.

Brute-force is not the correct answer, because it is a broader term that encompasses different types of attacks that involve trying different variations of symbols or words until the correct password is found. Password spraying is a specific type of brute force attack that uses a single common password against multiple accounts⁵. The logs show that the attacker is using password spraying, not brute force in general, to try to gain access to the web server. Reference=1:Password spraying: An overview of password spraying attacks ... - Norton, 2:Security: Credential Stuffing vs. Password Spraying - Baeldung, 3:Brute Force Attack: A definition + 6 types to know |

Norton, 4:What is a Pass-the-Hash Attack? - CrowdStrike, 5:What is a Brute Force Attack? | Definition, Types & How It Works - Fortinet

QUESTION 30

After a recent vulnerability scan, a security engineer needs to harden the routers within the corporate network. Which of the following is the most appropriate to disable?

- A. Console access
- B. Routing protocols
- C. VLANs
- D. Web-based administration

Correct Answer: D

Section:

Explanation:

Web-based administration is a feature that allows users to configure and manage routers through a web browser interface. While this feature can provide convenience and ease of use, it can also pose a security risk, especially if the web interface is exposed to the internet or uses weak authentication or encryption methods. Web-based administration can be exploited by attackers to gain unauthorized access to the router's settings, firmware, or data, or to launch attacks such as cross-site scripting (XSS) or cross-site request forgery (CSRF). Therefore, disabling web-based administration is a good practice to harden the routers within the corporate network. Console access, routing protocols, and VLANs are other features that can be configured on routers, but they are not the most appropriate to disable for hardening purposes. Console access is a physical connection to the router that requires direct access to the device, which can be secured by locking the router in a cabinet or using a strong password. Routing protocols are essential for routers to exchange routing information and maintain network connectivity, and they can be secured by using authentication or encryption mechanisms. VLANs are logical segments of a network that can enhance network performance and security by isolating traffic and devices, and they can be secured by using VLAN access control lists (VACLs) or private VLANs (PVLANS).

Reference:CCNA SEC: Router HardeningYour Router's Security Stinks: Here's How to Fix It

QUESTION 31

Which of the following is used to protect a computer from viruses, malware, and Trojans being installed and moving laterally across the network?

- A. IDS
- B. ACL
- C. EDR
- D. NAC

Correct Answer: C

Section:

Explanation:

Endpoint detection and response (EDR) is a technology that monitors and analyzes the activity and behavior of endpoints, such as computers, laptops, mobile devices, and servers. EDR can help to detect and prevent malicious software, such as viruses, malware, and Trojans, from infecting the endpoints and spreading across the network. EDR can also provide visibility and response capabilities to contain and remediate threats. EDR is different from IDS, which is a network-based technology that monitors and alerts on network traffic anomalies. EDR is also different from ACL, which is a list of rules that control the access to network resources.EDR is also different from NAC, which is a technology that enforces policies on the network access of devices based on their identity and compliance status.Reference:CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, page 2561

QUESTION 32

A systems administrator set up a perimeter firewall but continues to notice suspicious connections between internal endpoints. Which of the following should be set up in order to mitigate the threat posed by the suspicious activity?

- A. Host-based firewall
- B. Web application firewall
- C. Access control list
- D. Application allow list

Correct Answer: A

Section:

Explanation:

A host-based firewall is a software application that runs on an individual endpoint and filters the incoming and outgoing network traffic based on a set of rules. A host-based firewall can help to mitigate the threat posed by suspicious connections between internal endpoints by blocking or allowing the traffic based on the source, destination, port, protocol, or application. A host-based firewall is different from a web application firewall, which is



a type of firewall that protects web applications from common web-based attacks, such as SQL injection, cross-site scripting, and session hijacking. A host-based firewall is also different from an access control list, which is a list of rules that control the access to network resources, such as files, folders, printers, or routers. A host-based firewall is also different from an application allow list, which is a list of applications that are authorized to run on an endpoint, preventing unauthorized or malicious applications from executing. Reference: CompTIA Security+ Study Guide: Exam SY0-701, 9th Edition, page 254

QUESTION 33

A security analyst is reviewing alerts in the SIEM related to potential malicious network traffic coming from an employee's corporate laptop. The security analyst has determined that additional data about the executable running on the machine is necessary to continue the investigation. Which of the following logs should the analyst use as a data source?

- A. Application
- B. IPS/IDS
- C. Network
- D. Endpoint

Correct Answer: D

Section:

Explanation:

An endpoint log is a file that contains information about the activities and events that occur on an end-user device, such as a laptop, desktop, tablet, or smartphone. Endpoint logs can provide valuable data for security analysts, such as the processes running on the device, the network connections established, the files accessed or modified, the user actions performed, and the applications installed or updated. Endpoint logs can also record the details of any executable files running on the device, such as the name, path, size, hash, signature, and permissions of the executable.

An application log is a file that contains information about the events that occur within a software application, such as errors, warnings, transactions, or performance metrics. Application logs can help developers and administrators troubleshoot issues, optimize performance, and monitor user behavior. However, application logs may not provide enough information about the executable files running on the device, especially if they are malicious or unknown.

An IPS/IDS log is a file that contains information about the network traffic that is monitored and analyzed by an intrusion prevention system (IPS) or an intrusion detection system (IDS). IPS/IDS logs can help security analysts identify and block potential attacks, such as exploit attempts, denial-of-service (DoS) attacks, or malicious scans. However, IPS/IDS logs may not provide enough information about the executable files running on the device, especially if they are encrypted, obfuscated, or use legitimate protocols.

A network log is a file that contains information about the network activity and communication that occurs between devices, such as IP addresses, ports, protocols, packets, or bytes. Network logs can help security analysts understand the network topology, traffic patterns, and bandwidth usage. However, network logs may not provide enough information about the executable files running on the device, especially if they are hidden, spoofed, or use proxy servers.

Therefore, the best log type to use as a data source for additional information about the executable running on the machine is the endpoint log, as it can provide the most relevant and detailed data about the executable file and its behavior.

Reference= <https://www.crowdstrike.com/cybersecurity-101/observability/application-log/>

<https://owasp.org/www-project-proactive-controls/v3/en/c9-security-logging>

QUESTION 34

A cyber operations team informs a security analyst about a new tactic malicious actors are using to compromise networks.

SIEM alerts have not yet been configured. Which of the following best describes what the security analyst should do to identify this behavior?

- A. [Digital forensics
- B. E-discovery
- C. Incident response
- D. Threat hunting

Correct Answer: D

Section:

Explanation:

Threat hunting is the process of proactively searching for signs of malicious activity or compromise in a network, rather than waiting for alerts or indicators of compromise (IOCs) to appear. Threat hunting can help identify new tactics, techniques, and procedures (TTPs) used by malicious actors, as well as uncover hidden or stealthy threats that may have evaded detection by security tools. Threat hunting requires a combination of skills, tools, and methodologies, such as hypothesis generation, data collection and analysis, threat intelligence, and incident response. Threat hunting can also help improve the security posture of an organization by providing feedback and recommendations for security improvements. Reference= CompTIA Security+ Certification Exam Objectives, Domain 4.1: Given a scenario, analyze potential indicators of malicious activity. CompTIA Security+ Study Guide

QUESTION 35

A company purchased cyber insurance to address items listed on the risk register. Which of the following strategies does this represent?

- A. Accept
- B. Transfer
- C. Mitigate
- D. Avoid

Correct Answer: B

Section:

Explanation:

Cyber insurance is a type of insurance that covers the financial losses and liabilities that result from cyberattacks, such as data breaches, ransomware, denial-of-service, phishing, or malware. Cyber insurance can help a company recover from the costs of restoring data, repairing systems, paying ransoms, compensating customers, or facing legal actions. Cyber insurance is one of the possible strategies that a company can use to address the items listed on the risk register. A risk register is a document that records the identified risks, their probability, impact, and mitigation strategies for a project or an organization. The four common risk mitigation strategies are:
Accept: The company acknowledges the risk and decides to accept the consequences without taking any action to reduce or eliminate the risk. This strategy is usually chosen when the risk is low or the cost of mitigation is too high.

Transfer: The company transfers the risk to a third party, such as an insurance company, a vendor, or a partner. This strategy is usually chosen when the risk is high or the company lacks the resources or expertise to handle the risk.

Mitigate: The company implements controls or measures to reduce the likelihood or impact of the risk. This strategy is usually chosen when the risk is moderate or the cost of mitigation is reasonable.

Avoid: The company eliminates the risk by changing the scope, plan, or design of the project or the organization. This strategy is usually chosen when the risk is unacceptable or the cost of mitigation is too high.

By purchasing cyber insurance, the company is transferring the risk to the insurance company, which will cover the financial losses and liabilities in case of a cyberattack. Therefore, the correct answer is B.

Reference=CompTIA Security+ Study Guide (SY0-701), Chapter 8: Governance, Risk, and Compliance, page 377. Professor Messer's CompTIA SY0-701 Security+ Training Course, Section 8.1: Risk Management, video: Risk Mitigation Strategies (5:37).

QUESTION 36

A security administrator would like to protect data on employees' laptops. Which of the following encryption techniques should the security administrator use?

- A. Partition
- B. Asymmetric
- C. Full disk
- D. Database

Correct Answer: C

Section:

Explanation:

Full disk encryption (FDE) is a technique that encrypts all the data on a hard drive, including the operating system, applications, and files. FDE protects the data from unauthorized access in case the laptop is lost, stolen, or disposed of without proper sanitization. FDE requires the user to enter a password, a PIN, a smart card, or a biometric factor to unlock the drive and boot the system. FDE can be implemented by using software solutions, such as BitLocker, FileVault, or VeraCrypt, or by using hardware solutions, such as self-encrypting drives (SEDs) or Trusted Platform Modules (TPMs). FDE is a recommended encryption technique for laptops and other mobile devices that store sensitive data.

Partition encryption is a technique that encrypts only a specific partition or volume on a hard drive, leaving the rest of the drive unencrypted. Partition encryption is less secure than FDE, as it does not protect the entire drive and may leave traces of data on unencrypted areas. Partition encryption is also less convenient than FDE, as it requires the user to mount and unmount the encrypted partition manually.

Asymmetric encryption is a technique that uses a pair of keys, one public and one private, to encrypt and decrypt data. Asymmetric encryption is mainly used for securing communication, such as email, web, or VPN, rather than for encrypting data at rest. Asymmetric encryption is also slower and more computationally intensive than symmetric encryption, which is the type of encryption used by FDE and partition encryption.

Database encryption is a technique that encrypts data stored in a database, such as tables, columns, rows, or cells. Database encryption can be done at the application level, the database level, or the file system level.

Database encryption is useful for protecting data from unauthorized access by database administrators, hackers, or malware, but it does not protect the data from physical theft or loss of the device that hosts the database.

Reference=Data Encryption -- CompTIA Security+ SY0-401: 4.4, CompTIA Security+ Cheat Sheet and PDF | Zero To Mastery, CompTIA Security+ SY0-601 Certification Course - Cybr, Application Hardening -- SY0-601 CompTIA Security+ : 3.2.

QUESTION 37

Which of the following security control types does an acceptable use policy best represent?

- A. Detective
- B. Compensating
- C. Corrective
- D. Preventive

Correct Answer: D

Section:

Explanation:

An acceptable use policy (AUP) is a set of rules that govern how users can access and use a corporate network or the internet. The AUP helps companies minimize their exposure to cyber security threats and limit other risks. The AUP also serves as a notice to users about what they are not allowed to do and protects the company against misuse of their network. Users usually have to acknowledge that they understand and agree to the rules before accessing the network¹.

An AUP best represents a preventive security control type, because it aims to deter or stop potential security incidents from occurring in the first place. A preventive control is proactive and anticipates possible threats and vulnerabilities, and implements measures to prevent them from exploiting or harming the system or the data. A preventive control can be physical, technical, or administrative in nature².

Some examples of preventive controls are:

Locks, fences, or guards that prevent unauthorized physical access to a facility or a device

Firewalls, antivirus software, or encryption that prevent unauthorized logical access to a network or a system

Policies, procedures, or training that prevent unauthorized or inappropriate actions or behaviors by users or employees

An AUP is an example of an administrative preventive control, because it defines the policies and procedures that users must follow to ensure the security and proper use of the network and the IT resources. An AUP can prevent users from engaging in activities that could compromise the security, performance, or availability of the network or the system, such as:

Downloading or installing unauthorized or malicious software

Accessing or sharing sensitive or confidential information without authorization or encryption

Using the network or the system for personal, illegal, or unethical purposes

Bypassing or disabling security controls or mechanisms

Connecting unsecured or unapproved devices to the network

By enforcing an AUP, a company can prevent or reduce the likelihood of security breaches, data loss, legal liability, or reputational damage caused by user actions or inactions³.

Reference=¹:How to Create an Acceptable Use Policy - CoreTech,²: [Security Control Types: Preventive, Detective, Corrective, and Compensating],³:Why You Need A Corporate Acceptable Use Policy - CompTIA

QUESTION 38

An IT manager informs the entire help desk staff that only the IT manager and the help desk lead will have access to the administrator console of the help desk software. Which of the following security techniques is the IT manager setting up?

- A. Hardening
- B. Employee monitoring
- C. Configuration enforcement
- D. Least privilege

Correct Answer: D

Section:

Explanation:

The principle of least privilege is a security concept that limits access to resources to the minimum level needed for a user, a program, or a device to perform a legitimate function. It is a cybersecurity best practice that protects high-value data and assets from compromise or insider threat. Least privilege can be applied to different abstraction layers of a computing environment, such as processes, systems, or connected devices. However, it is rarely implemented in practice.

In this scenario, the IT manager is setting up the principle of least privilege by restricting access to the administrator console of the help desk software to only two authorized users: the IT manager and the help desk lead. This way, the IT manager can prevent unauthorized or accidental changes to the software configuration, data, or functionality by other help desk staff. The other help desk staff will only have access to the normal user interface of the software, which is sufficient for them to perform their job functions.

The other options are not correct. Hardening is the process of securing a system by reducing its surface of vulnerability, such as by removing unnecessary software, changing default passwords, or disabling unnecessary

services. Employee monitoring is the surveillance of workers' activity, such as by tracking web browsing, application use, keystrokes, or screenshots. Configuration enforcement is the process of ensuring that a system adheres to a predefined set of security settings, such as by applying a patch, a policy, or a template.

Reference=

https://en.wikipedia.org/wiki/Principle_of_least_privilege

https://en.wikipedia.org/wiki/Principle_of_least_privilege

QUESTION 39

Which of the following is the most likely to be used to document risks, responsible parties, and thresholds?

- A. Risk tolerance
- B. Risk transfer
- C. Risk register
- D. Risk analysis

Correct Answer: C

Section:

Explanation:

A risk register is a document that records and tracks the risks associated with a project, system, or organization. A risk register typically includes information such as the risk description, the risk owner, the risk probability, the risk impact, the risk level, the risk response strategy, and the risk status. A risk register can help identify, assess, prioritize, monitor, and control risks, as well as communicate them to relevant stakeholders. A risk register can also help document the risk tolerance and thresholds of an organization, which are the acceptable levels of risk exposure and the criteria for escalating or mitigating risks. Reference=CompTIA Security+ Certification Exam Objectives, Domain 5.1: Explain the importance of policies, plans, and procedures related to organizational security.CompTIA Security+ Study Guide (SY0-701), Chapter 5: Governance, Risk, and Compliance, page 211.CompTIA Security+ Certification Guide, Chapter 2: Risk Management, page 33.CompTIA Security+ Certification Exam SY0-701 Practice Test 1, Question 4.

QUESTION 40

Which of the following should a security administrator adhere to when setting up a new set of firewall rules?

- A. Disaster recovery plan
- B. Incident response procedure
- C. Business continuity plan
- D. Change management procedure

Correct Answer: D

Section:

Explanation:

A change management procedure is a set of steps and guidelines that a security administrator should adhere to when setting up a new set of firewall rules. A firewall is a device or software that can filter, block, or allow network traffic based on predefined rules or policies. A firewall rule is a statement that defines the criteria and action for a firewall to apply to a packet or a connection. For example, a firewall rule can allow or deny traffic based on the source and destination IP addresses, ports, protocols, or applications. Setting up a new set of firewall rules is a type of change that can affect the security, performance, and functionality of the network. Therefore, a change management procedure is necessary to ensure that the change is planned, tested, approved, implemented, documented, and reviewed in a controlled and consistent manner. A change management procedure typically includes the following elements:

A change request that describes the purpose, scope, impact, and benefits of the change, as well as the roles and responsibilities of the change owner, implementer, and approver.

A change assessment that evaluates the feasibility, risks, costs, and dependencies of the change, as well as the alternatives and contingency plans.

A change approval that authorizes the change to proceed to the implementation stage, based on the criteria and thresholds defined by the change policy.

A change implementation that executes the change according to the plan and schedule, and verifies the results and outcomes of the change.

A change documentation that records the details and status of the change, as well as the lessons learned and best practices.

A change review that monitors and measures the performance and effectiveness of the change, and identifies any issues or gaps that need to be addressed or improved.

A change management procedure is important for a security administrator to adhere to when setting up a new set of firewall rules, as it can help to achieve the following objectives:

Enhance the security posture and compliance of the network by ensuring that the firewall rules are aligned with the security policies and standards, and that they do not introduce any vulnerabilities or conflicts.

Minimize the disruption and downtime of the network by ensuring that the firewall rules are tested and validated before deployment, and that they do not affect the availability or functionality of the network services or applications.

Improve the efficiency and quality of the network by ensuring that the firewall rules are optimized and updated according to the changing needs and demands of the network users and stakeholders, and that they do not cause any performance or compatibility issues.

Increase the accountability and transparency of the network by ensuring that the firewall rules are documented and reviewed regularly, and that they are traceable and auditable by the relevant authorities and parties.

The other options are not correct because they are not related to the process of setting up a new set of firewall rules. A disaster recovery plan is a set of policies and procedures that aim to restore the normal operations of an organization in the event of a system failure, natural disaster, or other emergency. An incident response procedure is a set of steps and guidelines that aim to contain, analyze, eradicate, and recover from a security incident, such as a cyberattack, data breach, or malware infection. A business continuity plan is a set of strategies and actions that aim to maintain the essential functions and operations of an organization during and after a disruptive event, such as a pandemic, power outage, or civil unrest. Reference=CompTIA Security+ Study Guide (SY0-701), Chapter 7: Resilience and Recovery, page 325. Professor Messer's CompTIA SY0-701 Security+ Training Course, Section 1.3: Security Operations, video: Change Management (5:45).

QUESTION 41

A client asked a security company to provide a document outlining the project, the cost, and the completion time frame. Which of the following documents should the company provide to the client?

- A. MSA
- B. SLA
- C. BPA
- D. SOW

Correct Answer: D

Section:

Explanation:

An ISOW is a document that outlines the project, the cost, and the completion time frame for a security company to provide a service to a client. ISOW stands for Information Security Operations Work, and it is a type of contract that specifies the scope, deliverables, milestones, and payment terms of a security project. An ISOW is usually used for one-time or short-term projects that have a clear and defined objective and outcome. For example, an ISOW can be used for a security assessment, a penetration test, a security audit, or a security training.

The other options are not correct because they are not documents that outline the project, the cost, and the completion time frame for a security company to provide a service to a client. A MSA is a master service agreement, which is a type of contract that establishes the general terms and conditions for a long-term or ongoing relationship between a security company and a client. A MSA does not specify the details of each individual project, but rather sets the framework for future projects that will be governed by separate statements of work (SOWs). A SLA is a service level agreement, which is a type of contract that defines the quality and performance standards for a security service provided by a security company to a client. A SLA usually includes the metrics, targets, responsibilities, and penalties for measuring and ensuring the service level. A BPA is a business partnership agreement, which is a type of contract that establishes the roles and expectations for a strategic alliance between two or more security companies that collaborate to provide a joint service to a client. A BPA usually covers the objectives, benefits, risks, and obligations of the partnership. Reference=CompTIA Security+ Study Guide (SY0-701), Chapter 8: Governance, Risk, and Compliance, page 387. Professor Messer's CompTIA SY0-701 Security+ Training Course, Section 8.2: Compliance and Controls, video: Contracts and Agreements (5:12).

QUESTION 42

A security team is reviewing the findings in a report that was delivered after a third party performed a penetration test. One of the findings indicated that a web application form field is vulnerable to cross-site scripting. Which of the following application security techniques should the security analyst recommend the developer implement to prevent this vulnerability?

- A. Secure cookies
- B. Version control
- C. Input validation
- D. Code signing

Correct Answer: C

Section:

Explanation:

Input validation is a technique that checks the user input for any malicious or unexpected data before processing it by the web application. Input validation can prevent cross-site scripting (XSS) attacks, which exploit the vulnerability of a web application to execute malicious scripts in the browser of a victim. XSS attacks can compromise the confidentiality, integrity, and availability of the web application and its users. Input validation can be implemented on both the client-side and the server-side, but server-side validation is more reliable and secure. Input validation can use various methods, such as whitelisting, blacklisting, filtering, escaping, encoding, and sanitizing the input data. Reference=CompTIA Security+ Study Guide with over 500 Practice Test Questions: Exam SY0-701, 9th Edition, Chapter 2, page 70. CompTIA Security+ (SY0-701) Certification Exam Objectives, Domain 3.2, page 11. Application Security -- SY0-601 CompTIA Security+ : 3.2

QUESTION 43

Which of the following must be considered when designing a high-availability network? (Choose two).

- A. Ease of recovery
- B. Ability to patch
- C. Physical isolation
- D. Responsiveness
- E. Attack surface
- F. Extensible authentication

Correct Answer: A, E

Section:

Explanation:

A high-availability network is a network that is designed to minimize downtime and ensure continuous operation even in the event of a failure or disruption. A high-availability network must consider the following factors:

Ease of recovery: This refers to the ability of the network to restore normal functionality quickly and efficiently after a failure or disruption. Ease of recovery can be achieved by implementing backup and restore procedures, redundancy and failover mechanisms, fault tolerance and resilience, and disaster recovery plans.

Attack surface: This refers to the amount of exposure and vulnerability of the network to potential threats and attacks. Attack surface can be reduced by implementing security controls such as firewalls, encryption, authentication, access control, segmentation, and hardening.

The other options are not directly related to high-availability network design:

Ability to patch: This refers to the process of updating and fixing software components to address security issues, bugs, or performance improvements. Ability to patch is important for maintaining the security and functionality of the network, but it is not a specific factor for high-availability network design.

Physical isolation: This refers to the separation of network components or devices from other networks or physical environments. Physical isolation can enhance the security and performance of the network, but it can also reduce the availability and accessibility of the network resources.

Responsiveness: This refers to the speed and quality of the network's performance and service delivery. Responsiveness can be measured by metrics such as latency, throughput, jitter, and packet loss. Responsiveness is important for ensuring customer satisfaction and user experience, but it is not a specific factor for high-availability network design.

Extensible authentication: This refers to the ability of the network to support multiple and flexible authentication methods and protocols. Extensible authentication can improve the security and convenience of the network, but it is not a specific factor for high-availability network design.

Reference=1: CompTIA Security+ SY0-701 Certification Study Guide, page 972: High Availability -- CompTIA Security+ SY0-701 -- 3.4, video by Professor Messer.

QUESTION 44

A technician needs to apply a high-priority patch to a production system. Which of the following steps should be taken first?

- A. Air gap the system.
- B. Move the system to a different network segment.
- C. Create a change control request.
- D. Apply the patch to the system.

Correct Answer: C

Section:

Explanation:

= A change control request is a document that describes the proposed change to a system, the reason for the change, the expected impact, the approval process, the testing plan, the implementation plan, the rollback plan, and the communication plan. A change control request is a best practice for applying any patch to a production system, especially a high-priority one, as it ensures that the change is authorized, documented, tested, and communicated. A change control request also minimizes the risk of unintended consequences, such as system downtime, data loss, or security breaches. Reference=CompTIA Security+ Study Guide with over 500 Practice Test Questions: Exam SY0-701, 9th Edition, Chapter 6, page 235. CompTIA Security+ SY0-701 Exam Objectives, Domain 4.1, page 13.

QUESTION 45

Which of the following describes the reason root cause analysis should be conducted as part of incident response?

- A. To gather IoCs for the investigation
- B. To discover which systems have been affected
- C. To eradicate any trace of malware on the network
- D. To prevent future incidents of the same nature

Correct Answer: D

Section:

Explanation:

Root cause analysis is a process of identifying and resolving the underlying factors that led to an incident. By conducting root cause analysis as part of incident response, security professionals can learn from the incident and implement corrective actions to prevent future incidents of the same nature. For example, if the root cause of a data breach was a weak password policy, the security team can enforce a stronger password policy and educate users on the importance of password security. Root cause analysis can also help to improve security processes, policies, and procedures, and to enhance security awareness and culture within the organization. Root cause analysis is not meant to gather IoCs (indicators of compromise) for the investigation, as this is a task performed during the identification and analysis phases of incident response. Root cause analysis is also not meant to discover which systems have been affected or to eradicate any trace of malware on the network, as these are tasks performed during the containment and eradication phases of incident response. Reference=CompTIA Security+ SY0-701 Certification Study Guide, page 424-425; Professor Messer's CompTIA SY0-701 Security+ Training Course, video 5.1 - Incident Response, 9:55 - 11:18.

QUESTION 46

Which of the following is the most likely outcome if a large bank fails an internal PCI DSS compliance assessment?

- A. Fines
- B. Audit findings
- C. Sanctions
- D. Reputation damage

Correct Answer: A

Section:

Explanation:

PCI DSS is the Payment Card Industry Data Security Standard, which is a set of security requirements for organizations that store, process, or transmit cardholder data. PCI DSS aims to protect the confidentiality, integrity, and availability of cardholder data and prevent fraud, identity theft, and data breaches. PCI DSS is enforced by the payment card brands, such as Visa, Mastercard, American Express, Discover, and JCB, and applies to all entities involved in the payment card ecosystem, such as merchants, acquirers, issuers, processors, service providers, and payment applications.

If a large bank fails an internal PCI DSS compliance assessment, the most likely outcome is that the bank will face fines from the payment card brands. An internal PCI DSS compliance assessment is a self-assessment that the bank performs to evaluate its own compliance with the PCI DSS requirements. The bank must submit the results of the internal assessment to the payment card brands or their designated agents, such as acquirers or qualified security assessors (QSAs). If the internal assessment reveals that the bank is not compliant with the PCI DSS requirements, the payment card brands may impose fines on the bank as a penalty for violating the PCI DSS contract. The amount and frequency of the fines may vary depending on the severity and duration of the non-compliance, the number and type of cardholder data compromised, and the level of cooperation and remediation from the bank. The fines can range from thousands to millions of dollars per month, and can increase over time if the non-compliance is not resolved.

The other options are not correct because they are not the most likely outcomes if a large bank fails an internal PCI DSS compliance assessment. B. Audit findings. Audit findings are the results of an external PCI DSS compliance assessment that is performed by a QSA or an approved scanning vendor (ASV). An external assessment is required for certain entities that handle a large volume of cardholder data or have a history of non-compliance. An external assessment may also be triggered by a security incident or a request from the payment card brands. Audit findings may reveal the gaps and weaknesses in the bank's security controls and recommend corrective actions to achieve compliance. However, audit findings are not the outcome of an internal assessment, which is performed by the bank itself. C. Sanctions. Sanctions are the measures that the payment card brands may take against the bank if the bank fails to pay the fines or comply with the PCI DSS requirements. Sanctions may include increasing the fines, suspending or terminating the bank's ability to accept or process payment cards, or revoking the bank's PCI DSS certification. Sanctions are not the immediate outcome of an internal assessment, but rather the possible consequence of prolonged or repeated non-compliance. D. Reputation damage. Reputation damage is the loss of trust and credibility that the bank may suffer from its customers, partners, regulators, and the public if the bank fails an internal PCI DSS compliance assessment. Reputation damage may affect the bank's brand image, customer loyalty, market share, and profitability. Reputation damage is not a direct outcome of an internal assessment, but rather a potential risk that the bank may face if the non-compliance is exposed or exploited by malicious actors. Reference=CompTIA Security+ Study Guide (SY0-701), Chapter 8: Governance, Risk, and Compliance, page 388. Professor Messer's CompTIA SY0-701 Security+ Training Course, Section 8.2: Compliance and Controls, video: PCI DSS (5:12). PCI Security Standards Council, PCI DSS Quick Reference Guide, page 4. PCI Security Standards Council, PCI DSS FAQs, question 8. PCI Security Standards Council, PCI DSS FAQs, question 9. [PCI Security Standards Council], PCI DSS FAQs, question 10. [PCI Security Standards Council], PCI DSS FAQs, question 11. [PCI Security Standards Council], PCI DSS FAQs, question 12. [PCI Security Standards Council], PCI DSS FAQs, question 13. [PCI Security Standards Council], PCI DSS FAQs, question 14. [PCI Security Standards Council], PCI DSS FAQs, question 15. [PCI Security Standards Council], PCI DSS FAQs, question 16. [PCI Security Standards Council], PCI DSS FAQs, question 17. [PCI Security Standards Council], PCI DSS FAQs, question 18. [PCI Security Standards Council], PCI DSS FAQs, question 19. [PCI Security Standards Council], PCI DSS FAQs, question 20. [PCI Security Standards Council], PCI DSS FAQs, question 21. [PCI Security Standards Council], PCI DSS FAQs, question 22. [PCI Security Standards Council], PCI DSS FAQs, question 23. [PCI Security Standards Council], PCI DSS FAQs, question 24. [PCI Security Standards Council], PCI DSS FAQs, question 25. [PCI Security Standards Council], PCI DSS FAQs, question 26. [PCI Security Standards Council], PCI DSS FAQs, question 27. [PCI



Security Standards Council], PCI DSS FAQs, question 28. [PCI Security Standards Council], PCI DSS FAQs, question 29. [PCI Security Standards Council], PCI DSS FAQs, question 30. [PCI Security Standards Council]

QUESTION 47

A company is developing a business continuity strategy and needs to determine how many staff members would be required to sustain the business in the case of a disruption. Which of the following best describes this step?

- A. Capacity planning
- B. Redundancy
- C. Geographic dispersion
- D. Tablet exercise

Correct Answer: A

Section:

Explanation:

Capacity planning is the process of determining the resources needed to meet the current and future demands of an organization. Capacity planning can help a company develop a business continuity strategy by estimating how many staff members would be required to sustain the business in the case of a disruption, such as a natural disaster, a cyberattack, or a pandemic. Capacity planning can also help a company optimize the use of its resources, reduce costs, and improve performance. Reference=CompTIA Security+ Study Guide with over 500 Practice Test Questions: Exam SY0-701, 9th Edition, Chapter 4, page 184. CompTIA Security+ (SY0-701) Certification Exam Objectives, Domain 4.1, page 14. Business Continuity -- SY0-601 CompTIA Security+ : 4.1

QUESTION 48

A company's legal department drafted sensitive documents in a SaaS application and wants to ensure the documents cannot be accessed by individuals in high-risk countries. Which of the following is the most effective way to limit this access?

- A. Data masking
- B. Encryption
- C. Geolocation policy
- D. Data sovereignty regulation



Correct Answer: C

Section:

Explanation:

A geolocation policy is a policy that restricts or allows access to data or resources based on the geographic location of the user or device. A geolocation policy can be implemented using various methods, such as IP address filtering, GPS tracking, or geofencing. A geolocation policy can help the company's legal department to prevent unauthorized access to sensitive documents from individuals in high-risk countries¹².

The other options are not effective ways to limit access based on location:

Data masking: This is a technique of obscuring or replacing sensitive data with fictitious or anonymized data. Data masking can protect the privacy and confidentiality of data, but it does not prevent access to data based on location³.

Encryption: This is a process of transforming data into an unreadable format using a secret key or algorithm. Encryption can protect the integrity and confidentiality of data, but it does not prevent access to data based on location. Encryption can also be bypassed by attackers who have the decryption key or method⁴.

Data sovereignty regulation: This is a set of laws or rules that govern the storage, processing, and transfer of data within a specific jurisdiction or country. Data sovereignty regulation can affect the availability and compliance of data, but it does not prevent access to data based on location. Data sovereignty regulation can also vary depending on the country or region.

Reference=1: CompTIA Security+ SY0-701 Certification Study Guide, page 972: Account Policies -- SY0-601 CompTIA Security+ : 3.7, video by Professor Messer³: CompTIA Security+ SY0-701 Certification Study Guide, page 1004: CompTIA Security+ SY0-701 Certification Study Guide, page 101. : CompTIA Security+ SY0-701 Certification Study Guide, page 102.

QUESTION 49

Which of the following is a hardware-specific vulnerability?

- A. Firmware version
- B. Buffer overflow
- C. SQL injection

D. Cross-site scripting

Correct Answer: A

Section:

Explanation:

Firmware is a type of software that is embedded in a hardware device, such as a router, a printer, or a BIOS chip. Firmware controls the basic functions and operations of the device, and it can be updated or modified by the manufacturer or the user. Firmware version is a hardware-specific vulnerability, as it can expose the device to security risks if it is outdated, corrupted, or tampered with. An attacker can exploit firmware vulnerabilities to gain unauthorized access, modify device settings, install malware, or cause damage to the device or the network. Therefore, it is important to keep firmware updated and verify its integrity and authenticity. Reference=CompTIA Security+ Study Guide with over 500 Practice Test Questions: Exam SY0-701, 9th Edition, Chapter 2, page 67. CompTIA Security+ SY0-701 Exam Objectives, Domain 2.1, page 10.

QUESTION 50

While troubleshooting a firewall configuration, a technician determines that a "deny any" policy should be added to the bottom of the ACL. The technician updates the policy, but the new policy causes several company servers to become unreachable.

Which of the following actions would prevent this issue?

- A. Documenting the new policy in a change request and submitting the request to change management
- B. Testing the policy in a non-production environment before enabling the policy in the production network
- C. Disabling any intrusion prevention signatures on the 'deny any*' policy prior to enabling the new policy
- D. Including an 'allow any1 policy above the 'deny any*' policy

Correct Answer: B

Section:

Explanation:

A firewall policy is a set of rules that defines what traffic is allowed or denied on a network. A firewall policy should be carefully designed and tested before being implemented, as a misconfigured policy can cause network disruptions or security breaches. A common best practice is to test the policy in a non-production environment, such as a lab or a simulation, before enabling the policy in the production network. This way, the technician can verify the functionality and performance of the policy, and identify and resolve any issues or conflicts, without affecting the live network. Testing the policy in a non-production environment would prevent the issue of the 'deny any' policy causing several company servers to become unreachable, as the technician would be able to detect and correct the problem before applying the policy to the production network.

Documenting the new policy in a change request and submitting the request to change management is a good practice, but it would not prevent the issue by itself. Change management is a process that ensures that any changes to the network are authorized, documented, and communicated, but it does not guarantee that the changes are error-free or functional. The technician still needs to test the policy before implementing it.

Disabling any intrusion prevention signatures on the 'deny any' policy prior to enabling the new policy would not prevent the issue, and it could reduce the security of the network. Intrusion prevention signatures are patterns that identify malicious or unwanted traffic, and allow the firewall to block or alert on such traffic. Disabling these signatures would make the firewall less effective in detecting and preventing attacks, and it would not affect the reachability of the company servers.

Including an 'allow any' policy above the 'deny any' policy would not prevent the issue, and it would render the 'deny any' policy useless. A firewall policy is processed from top to bottom, and the first matching rule is applied. An 'allow any' policy would match any traffic and allow it to pass through the firewall, regardless of the source, destination, or protocol. This would negate the purpose of the 'deny any' policy, which is to block any traffic that does not match any of the previous rules. Moreover, an 'allow any' policy would create a security risk, as it would allow any unauthorized or malicious traffic to enter or exit the network. Reference=CompTIA Security+ SY0-701 Certification Study Guide, page 204-205; Professor Messer's CompTIA SY0-701 Security+ Training Course, video 2.1 - Network Security Devices, 8:00 - 10:00.

QUESTION 51

A software development manager wants to ensure the authenticity of the code created by the company. Which of the following options is the most appropriate?

- A. Testing input validation on the user input fields
- B. Performing code signing on company-developed software
- C. Performing static code analysis on the software
- D. Ensuring secure cookies are use

Correct Answer: B

Section:

Explanation:

Code signing is a technique that uses cryptography to verify the authenticity and integrity of the code created by the company. Code signing involves applying a digital signature to the code using a private key that only the

company possesses. The digital signature can be verified by anyone who has the corresponding public key, which can be distributed through a trusted certificate authority. Code signing can prevent unauthorized modifications, tampering, or malware injection into the code, and it can also assure the users that the code is from a legitimate source. Reference=CompTIA Security+ Study Guide with over 500 Practice Test Questions: Exam SY0-701, 9th Edition, Chapter 2, page 74. CompTIA Security+ (SY0-701) Certification Exam Objectives, Domain 3.2, page 11. Application Security -- SY0-601 CompTIA Security+ : 3.2

QUESTION 52

Which of the following can be used to identify potential attacker activities without affecting production servers?

- A. Honey pot
- B. Video surveillance
- C. Zero Trust
- D. Geofencing

Correct Answer: A

Section:

Explanation:

A honey pot is a system or a network that is designed to mimic a real production server and attract potential attackers. A honey pot can be used to identify the attacker's methods, techniques, and objectives without affecting the actual production servers. A honey pot can also divert the attacker's attention from the real targets and waste their time and resources¹².

The other options are not effective ways to identify potential attacker activities without affecting production servers:

Video surveillance: This is a physical security technique that uses cameras and monitors to record and observe the activities in a certain area. Video surveillance can help to deter, detect, and investigate physical intrusions, but it does not directly identify the attacker's activities on the network or the servers³.

Zero Trust: This is a security strategy that assumes that no user, device, or network is trustworthy by default and requires strict verification and validation for every request and transaction. Zero Trust can help to improve the security posture and reduce the attack surface of an organization, but it does not directly identify the attacker's activities on the network or the servers⁴.

Geofencing: This is a security technique that uses geographic location as a criterion to restrict or allow access to data or resources. Geofencing can help to protect the data sovereignty and compliance of an organization, but it does not directly identify the attacker's activities on the network or the servers⁵.

Reference=1: CompTIA Security+ SY0-701 Certification Study Guide, page 542: Honey pots and Deception -- SY0-601 CompTIA Security+ : 2.1, video by Professor Messer³: CompTIA Security+ SY0-701 Certification Study Guide, page 974: CompTIA Security+ SY0-701 Certification Study Guide, page 985: CompTIA Security+ SY0-701 Certification Study Guide, page 99.

QUESTION 53

During an investigation, an incident response team attempts to understand the source of an incident. Which of the following incident response activities describes this process?

- A. Analysis
- B. Lessons learned
- C. Detection
- D. Containment

Correct Answer: A

Section:

Explanation:

Analysis is the incident response activity that describes the process of understanding the source of an incident. Analysis involves collecting and examining evidence, identifying the root cause, determining the scope and impact, and assessing the threat actor's motives and capabilities. Analysis helps the incident response team to formulate an appropriate response strategy, as well as to prevent or mitigate future incidents. Analysis is usually performed after detection and before containment, eradication, recovery, and lessons learned. Reference=CompTIA Security+ Study Guide with over 500 Practice Test Questions: Exam SY0-701, 9th Edition, Chapter 6, page 223. CompTIA Security+ SY0-701 Exam Objectives, Domain 4.2, page 13.

QUESTION 54

A security practitioner completes a vulnerability assessment on a company's network and finds several vulnerabilities, which the operations team remediates. Which of the following should be done next?

- A. Conduct an audit.
- B. Initiate a penetration test.

- C. Rescan the network.
- D. Submit a report.

Correct Answer: C

Section:

Explanation:

After completing a vulnerability assessment and remediating the identified vulnerabilities, the next step is to rescan the network to verify that the vulnerabilities have been successfully fixed and no new vulnerabilities have been introduced. A vulnerability assessment is a process of identifying and evaluating the weaknesses and exposures in a network, system, or application that could be exploited by attackers. A vulnerability assessment typically involves using automated tools, such as scanners, to scan the network and generate a report of the findings. The report may include information such as the severity, impact, and remediation of the vulnerabilities. The operations team is responsible for applying the appropriate patches, updates, or configurations to address the vulnerabilities and reduce the risk to the network. A rescan is necessary to confirm that the remediation actions have been effective and that the network is secure.

Conducting an audit, initiating a penetration test, or submitting a report are not the next steps after completing a vulnerability assessment and remediating the vulnerabilities. An audit is a process of reviewing and verifying the compliance of the network with the established policies, standards, and regulations. An audit may be performed by internal or external auditors, and it may use the results of the vulnerability assessment as part of the evidence. However, an audit is not a mandatory step after a vulnerability assessment, and it does not validate the effectiveness of the remediation actions.

A penetration test is a process of simulating a real-world attack on the network to test the security defenses and identify any gaps or weaknesses. A penetration test may use the results of the vulnerability assessment as a starting point, but it goes beyond scanning and involves exploiting the vulnerabilities to gain access or cause damage. A penetration test may be performed after a vulnerability assessment, but only with the proper authorization, scope, and rules of engagement. A penetration test is not a substitute for a rescan, as it does not verify that the vulnerabilities have been fixed.

Submitting a report is a step that is done after the vulnerability assessment, but before the remediation. The report is a document that summarizes the findings and recommendations of the vulnerability assessment, and it is used to communicate the results to the stakeholders and the operations team. The report may also include a follow-up plan and a timeline for the remediation actions. However, submitting a report is not the final step after the remediation, as it does not confirm that the network is secure.

Reference=CompTIA Security+ SY0-701 Certification Study Guide, page 372-375;Professor Messer's CompTIA SY0-701 Security+ Training Course, video 4.1 - Vulnerability Scanning, 0:00 - 8:00.

QUESTION 55

An administrator was notified that a user logged in remotely after hours and copied large amounts of data to a personal device.

Which of the following best describes the user's activity?

- A. Penetration testing
- B. Phishing campaign
- C. External audit
- D. Insider threat

Correct Answer: D

Section:

Explanation:

An insider threat is a security risk that originates from within the organization, such as an employee, contractor, or business partner, who has authorized access to the organization's data and systems. An insider threat can be malicious, such as stealing, leaking, or sabotaging sensitive data, or unintentional, such as falling victim to phishing or social engineering. An insider threat can cause significant damage to the organization's reputation, finances, operations, and legal compliance. The user's activity of logging in remotely after hours and copying large amounts of data to a personal device is an example of a malicious insider threat, as it violates the organization's security policies and compromises the confidentiality and integrity of the data. Reference=Insider Threats -- CompTIA Security+ SY0-701: 3.2, video at 0:00;CompTIA Security+ SY0-701 Certification Study Guide, page 133.

QUESTION 56

Which of the following allows for the attribution of messages to individuals?

- A. Adaptive identity
- B. Non-repudiation
- C. Authentication
- D. Access logs

Correct Answer: B

Section:

Explanation:

Non-repudiation is the ability to prove that a message or document was sent or signed by a particular person, and that the person cannot deny sending or signing it. Non-repudiation can be achieved by using cryptographic techniques, such as hashing and digital signatures, that can verify the authenticity and integrity of the message or document. Non-repudiation can be useful for legal, financial, or contractual purposes, as it can provide evidence of the origin and content of the message or document. Reference=Non-repudiation -- CompTIA Security+ SY0-701 -- 1.2, CompTIA Security+ SY0-301: 6.1 -- Non-repudiation, CompTIA Security+ (SY0-701) Certification Exam Objectives, Domain 1.2, page 2.

QUESTION 57

Which of the following is the best way to consistently determine on a daily basis whether security settings on servers have been modified?

- A. Automation
- B. Compliance checklist
- C. Attestation
- D. Manual audit

Correct Answer: A

Section:

Explanation:

Automation is the best way to consistently determine on a daily basis whether security settings on servers have been modified. Automation is the process of using software, hardware, or other tools to perform tasks that would otherwise require human intervention or manual effort. Automation can help to improve the efficiency, accuracy, and consistency of security operations, as well as reduce human errors and costs. Automation can be used to monitor, audit, and enforce security settings on servers, such as firewall rules, encryption keys, access controls, patch levels, and configuration files. Automation can also alert security personnel of any changes or anomalies that may indicate a security breach or compromise¹².

The other options are not the best ways to consistently determine on a daily basis whether security settings on servers have been modified:

Compliance checklist: This is a document that lists the security requirements, standards, or best practices that an organization must follow or adhere to. A compliance checklist can help to ensure that the security settings on servers are aligned with the organizational policies and regulations, but it does not automatically detect or report any changes or modifications that may occur on a daily basis³.

Attestation: This is a process of verifying or confirming the validity or accuracy of a statement, claim, or fact. Attestation can be used to provide assurance or evidence that the security settings on servers are correct and authorized, but it does not continuously monitor or audit any changes or modifications that may occur on a daily basis⁴.

Manual audit: This is a process of examining or reviewing the security settings on servers by human inspectors or auditors. A manual audit can help to identify and correct any security issues or discrepancies on servers, but it is time-consuming, labor-intensive, and prone to human errors. A manual audit may not be feasible or practical to perform on a daily basis.

Reference=1: CompTIA Security+ SY0-701 Certification Study Guide, page 1022: Automation and Scripting -- CompTIA Security+ SY0-701 -- 5.1, video by Professor Messer³: CompTIA Security+ SY0-701 Certification Study Guide, page 974: CompTIA Security+ SY0-701 Certification Study Guide, page 98. : CompTIA Security+ SY0-701 Certification Study Guide, page 99.

QUESTION 58

Which of the following tools can assist with detecting an employee who has accidentally emailed a file containing a customer's PII?

- A. SCAP
- B. Net Flow
- C. Antivirus
- D. DLP

Correct Answer: D

Section:

Explanation:

DLP stands for Data Loss Prevention, which is a tool that can assist with detecting and preventing the unauthorized transmission or leakage of sensitive data, such as a customer's PII (Personally Identifiable Information). DLP can monitor, filter, and block data in motion (such as emails), data at rest (such as files), and data in use (such as applications). DLP can also alert the sender, the recipient, or the administrator of the data breach, and apply remediation actions, such as encryption, quarantine, or deletion. DLP can help an organization comply with data protection regulations, such as GDPR, HIPAA, or PCI DSS, and protect its reputation and assets. Reference=CompTIA Security+ Study Guide with over 500 Practice Test Questions: Exam SY0-701, 9th Edition, Chapter 2, page 78. CompTIA Security+ SY0-701 Exam Objectives, Domain 2.5, page 11.

QUESTION 59

An organization recently updated its security policy to include the following statement:

Regular expressions are included in source code to remove special characters such as \$, |, ;, &, `, and ? from variables set by forms in a web application.

Which of the following best explains the security technique the organization adopted by making this addition to the policy?

- A. Identify embedded keys
- B. Code debugging
- C. Input validation
- D. Static code analysis

Correct Answer: C

Section:

Explanation:

Input validation is a security technique that checks the user input for any malicious or unexpected data before processing it by the application. Input validation can prevent various types of attacks, such as injection, cross-site scripting, buffer overflow, and command execution, that exploit the vulnerabilities in the application code. Input validation can be performed on both the client-side and the server-side, using methods such as whitelisting, blacklisting, filtering, sanitizing, escaping, and encoding. By including regular expressions in the source code to remove special characters from the variables set by the forms in the web application, the organization adopted input validation as a security technique. Regular expressions are patterns that match a specific set of characters or strings, and can be used to filter out any unwanted or harmful input. Special characters, such as \$, |, ;, &, `, and ?, can be used by attackers to inject commands or scripts into the application, and cause damage or data theft. By removing these characters from the input, the organization can reduce the risk of such attacks.

Identify embedded keys, code debugging, and static code analysis are not the security techniques that the organization adopted by making this addition to the policy. Identify embedded keys is a process of finding and removing any hard-coded keys or credentials from the source code, as these can pose a security risk if exposed or compromised. Code debugging is a process of finding and fixing any errors or bugs in the source code, which can affect the functionality or performance of the application. Static code analysis is a process of analyzing the source code without executing it, to identify any vulnerabilities, flaws, or coding standards violations. These techniques are not related to the use of regular expressions to remove special characters from the input.

Reference = CompTIA Security+ SY0-701 Certification Study Guide, page 375-376; Professor Messer's CompTIA SY0-701 Security+ Training Course, video 4.1 - Vulnerability Scanning, 8:00 - 9:08; Application Security -- SY0-601 CompTIA Security+ : 3.2, 0:00 - 2:00.



QUESTION 60

A security analyst and the management team are reviewing the organizational performance of a recent phishing campaign. The user click-through rate exceeded the acceptable risk threshold, and the management team wants to reduce the impact when a user clicks on a link in a phishing message. Which of the following should the analyst do?

- A. Place posters around the office to raise awareness of common phishing activities.
- B. Implement email security filters to prevent phishing emails from being delivered
- C. Update the EDR policies to block automatic execution of downloaded programs.
- D. Create additional training for users to recognize the signs of phishing attempts.

Correct Answer: C

Section:

Explanation:

An endpoint detection and response (EDR) system is a security tool that monitors and analyzes the activities and behaviors of endpoints, such as computers, laptops, mobile devices, and servers. An EDR system can detect, prevent, and respond to various types of threats, such as malware, ransomware, phishing, and advanced persistent threats (APTs). One of the features of an EDR system is to block the automatic execution of downloaded programs, which can prevent malicious code from running on the endpoint when a user clicks on a link in a phishing message. This can reduce the impact of a phishing attack and protect the endpoint from compromise. Updating the EDR policies to block automatic execution of downloaded programs is a technical control that can mitigate the risk of phishing, regardless of the user's awareness or behavior. Therefore, this is the best answer among the given options.

The other options are not as effective as updating the EDR policies, because they rely on administrative or physical controls that may not be sufficient to prevent or stop a phishing attack. Placing posters around the office to raise awareness of common phishing activities is a physical control that can increase the user's knowledge of phishing, but it may not change their behavior or prevent them from clicking on a link in a phishing message.

Implementing email security filters to prevent phishing emails from being delivered is an administrative control that can reduce the exposure to phishing, but it may not be able to block all phishing emails, especially if they are crafted to bypass the filters. Creating additional training for users to recognize the signs of phishing attempts is an administrative control that can improve the user's skills of phishing detection, but it may not guarantee that they will always be vigilant or cautious when receiving an email. Therefore, these options are not the best answer for this question. Reference=Endpoint Detection and Response -- CompTIA Security+ SY0-701 -- 2.2, video at 5:30;CompTIA Security+ SY0-701 Certification Study Guide, page 163.

QUESTION 61

A company decided to reduce the cost of its annual cyber insurance policy by removing the coverage for ransomware attacks. Which of the following analysis elements did the company most likely use in making this decision?

- A. IMTTR
- B. RTO
- C. ARO
- D. MTBF

Correct Answer: C

Section:

Explanation:

ARO (Annualized Rate of Occurrence) is an analysis element that measures the frequency or likelihood of an event happening in a given year. ARO is often used in risk assessment and management, as it helps to estimate the potential loss or impact of an event. A company can use ARO to calculate the annualized loss expectancy (ALE) of an event, which is the product of ARO and the single loss expectancy (SLE). ALE represents the expected cost of an event per year, and can be used to compare with the cost of implementing a security control or purchasing an insurance policy.

The company most likely used ARO in making the decision to remove the coverage for ransomware attacks from its cyber insurance policy. The company may have estimated the ARO of ransomware attacks based on historical data, industry trends, or threat intelligence, and found that the ARO was low or negligible. The company may have also calculated the ALE of ransomware attacks, and found that the ALE was lower than the cost of the insurance policy. Therefore, the company decided to reduce the cost of its annual cyber insurance policy by removing the coverage for ransomware attacks, as it deemed the risk to be acceptable or manageable.

IMTTR (Incident Management Team Training and Readiness), RTO (Recovery Time Objective), and MTBF (Mean Time Between Failures) are not analysis elements that the company most likely used in making the decision to remove the coverage for ransomware attacks from its cyber insurance policy. IMTTR is a process of preparing and training the incident management team to respond effectively to security incidents. IMTTR does not measure the frequency or impact of an event, but rather the capability and readiness of the team. RTO is a metric that defines the maximum acceptable time for restoring a system or service after a disruption. RTO does not measure the frequency or impact of an event, but rather the availability and continuity of the system or service. MTBF is a metric that measures the average time between failures of a system or component. MTBF does not measure the frequency or impact of an event, but rather the reliability and performance of the system or component.

Reference=CompTIA Security+ SY0-701 Certification Study Guide, page 97-98;Professor Messer's CompTIA SY0-701 Security+ Training Course, video 5.2 - Risk Management, 0:00 - 3:00.

QUESTION 62

Which of the following is the most likely to be included as an element of communication in a security awareness program?

- A. Reporting phishing attempts or other suspicious activities
- B. Detecting insider threats using anomalous behavior recognition
- C. Verifying information when modifying wire transfer data
- D. Performing social engineering as part of third-party penetration testing

Correct Answer: A

Section:

Explanation:

A security awareness program is a set of activities and initiatives that aim to educate and inform the users and employees of an organization about the security policies, procedures, and best practices. A security awareness program can help to reduce the human factor in security risks, such as social engineering, phishing, malware, data breaches, and insider threats. A security awareness program should include various elements of communication, such as newsletters, posters, videos, webinars, quizzes, games, simulations, and feedback mechanisms, to deliver the security messages and reinforce the security culture. One of the most likely elements of communication to be included in a security awareness program is reporting phishing attempts or other suspicious activities, as this can help to raise the awareness of the users and employees about the common types of cyberattacks and how to respond to them. Reporting phishing attempts or other suspicious activities can also help to alert the security team and enable them to take appropriate actions to prevent or mitigate the impact of the attacks. Therefore, this is the best answer among the given options.

The other options are not as likely to be included as elements of communication in a security awareness program, because they are either technical or operational tasks that are not directly related to the security awareness of the users and employees. Detecting insider threats using anomalous behavior recognition is a technical task that involves using security tools or systems to monitor and analyze the activities and behaviors of the users and employees and identify any deviations or anomalies that may indicate malicious or unauthorized actions. This task is usually performed by the security team or the security operations center, and it does not require the communication or participation of the users and employees. Verifying information when modifying wire transfer data is an operational task that involves using verification methods, such as phone calls, emails, or digital signatures, to confirm the authenticity and accuracy of the information related to wire transfers, such as the account number, the amount, or the recipient. This task is usually performed by the financial or accounting department, and it does not involve the security awareness of the users and employees. Performing social engineering as part of third-party penetration testing is a technical task that involves using deception or manipulation techniques, such as phishing, vishing, or impersonation, to test the security posture and the vulnerability of the users and employees to social engineering attacks. This task is usually performed by external security

professionals or consultants, and it does not require the communication or consent of the users and employees. Therefore, these options are not the best answer for this question. Reference=Security Awareness and Training -
- CompTIA Security+ SY0-701: 5.2, video at 0:00;CompTIA Security+ SY0-701 Certification Study Guide, page 263.

QUESTION 63

HOTSPOT

Select the appropriate attack and remediation from each drop-down list to label the corresponding attack with its remediation.

INSTRUCTIONS

Not all attacks and remediation actions will be used.

If at any time you would like to bring back the initial state of the simulation, please click the Reset All button.

Hot Area:



Attack Description	Target	Attack Identified	BEST Preventative or Remediation Action
An attacker sends multiple SYN packets from multiple sources.	Web server	<ul style="list-style-type: none"> Botnet RAT Logic Bomb Backdoor Virus Spyware Worm Adware Ransomware Keylogger Phishing 	<ul style="list-style-type: none"> Enable DDoS protection Patch vulnerable systems Disable vulnerable services Change the default system password Update the cryptographic algorithms Change the default application password Implement 2FA using push notification Conduct a code review Implement application fuzzing Implement a host-based IPS Disable remote access services
The attack establishes a connection, which allows remote commands to be executed.	User	<ul style="list-style-type: none"> Botnet RAT Logic Bomb Backdoor Virus Spyware Worm Adware Ransomware Keylogger Phishing 	<ul style="list-style-type: none"> Enable DDoS protection Patch vulnerable systems Disable vulnerable services Change the default system password Update the cryptographic algorithms Change the default application password Implement 2FA using push notification Conduct a code review Implement application fuzzing Implement a host-based IPS Disable remote access services
The attack is self propagating and compromises a SQL database using well-known credentials as it moves through the network.	Database server	<ul style="list-style-type: none"> Botnet RAT Logic Bomb Backdoor Virus Spyware Worm Adware Ransomware Keylogger Phishing 	<ul style="list-style-type: none"> Enable DDoS protection Patch vulnerable systems Disable vulnerable services Change the default system password Update the cryptographic algorithms Change the default application password Implement 2FA using push notification Conduct a code review Implement application fuzzing Implement a host-based IPS Disable remote access services
The attacker uses hardware to remotely monitor a user's input activity to harvest credentials.	Executive	<ul style="list-style-type: none"> Botnet RAT Logic Bomb Backdoor Virus Spyware Worm Adware Ransomware Keylogger Phishing 	<ul style="list-style-type: none"> Enable DDoS protection Patch vulnerable systems Disable vulnerable services Change the default system password Update the cryptographic algorithms Change the default application password Implement 2FA using push notification Conduct a code review Implement application fuzzing Implement a host-based IPS Disable remote access services
The attacker embeds hidden access in an internally developed application that bypasses account login.	Application	<ul style="list-style-type: none"> Botnet RAT Logic Bomb Backdoor Virus Spyware 	<ul style="list-style-type: none"> Enable DDoS protection Patch vulnerable systems Disable vulnerable services Change the default system password Update the cryptographic algorithms Change the default application password Implement 2FA using push notification Conduct a code review Implement application fuzzing Implement a host-based IPS Disable remote access services



Answer Area:



Attack Description	Target	Attack Identified	BEST Preventative or Remediation Action
An attacker sends multiple SYN packets from multiple sources.	Web server	<ul style="list-style-type: none"> Botnet RAT Logic Bomb Backdoor Virus Spyware Worm Adware Ransomware Keylogger Phishing 	<ul style="list-style-type: none"> Enable DDoS protection Patch vulnerable systems Disable vulnerable services Change the default system password Update the cryptographic algorithms Change the default application password Implement 2FA using push notification Conduct a code review Implement application fuzzing Implement a host-based IPS Disable remote access services
The attack establishes a connection, which allows remote commands to be executed.	User	<ul style="list-style-type: none"> Botnet RAT Logic Bomb Backdoor Virus Spyware Worm Adware Ransomware Keylogger Phishing 	<ul style="list-style-type: none"> Enable DDoS protection Patch vulnerable systems Disable vulnerable services Change the default system password Update the cryptographic algorithms Change the default application password Implement 2FA using push notification Conduct a code review Implement application fuzzing Implement a host-based IPS Disable remote access services
The attack is self propagating and compromises a SQL database using well-known credentials as it moves through the network.	Database server	<ul style="list-style-type: none"> Botnet RAT Logic Bomb Backdoor Virus Spyware Worm Adware Ransomware Keylogger Phishing 	<ul style="list-style-type: none"> Enable DDoS protection Patch vulnerable systems Disable vulnerable services Change the default system password Update the cryptographic algorithms Change the default application password Implement 2FA using push notification Conduct a code review Implement application fuzzing Implement a host-based IPS Disable remote access services
The attacker uses hardware to remotely monitor a user's input activity to harvest credentials.	Executive	<ul style="list-style-type: none"> Botnet RAT Logic Bomb Backdoor Virus Spyware Worm Adware Ransomware Keylogger Phishing 	<ul style="list-style-type: none"> Enable DDoS protection Patch vulnerable systems Disable vulnerable services Change the default system password Update the cryptographic algorithms Change the default application password Implement 2FA using push notification Conduct a code review Implement application fuzzing Implement a host-based IPS Disable remote access services
The attacker embeds hidden access in an internally developed application that bypasses account login.	Application	<ul style="list-style-type: none"> Botnet RAT Logic Bomb Backdoor Virus Spyware 	<ul style="list-style-type: none"> Enable DDoS protection Patch vulnerable systems Disable vulnerable services Change the default system password Update the cryptographic algorithms Change the default application password

Section:**Explanation:**

Web server Botnet Enable DDoS protection

User RAT Implement a host-based IPS

Database server Worm Change the default application password

Executive Keylogger Disable vulnerable services

Application Backdoor Implement 2FA using push notification

QUESTION 64

After a recent ransomware attack on a company's system, an administrator reviewed the log files. Which of the following control types did the administrator use?

- A. Compensating
- B. Detective
- C. Preventive
- D. Corrective

Correct Answer: B

Section:**Explanation:**

Detective controls are security measures that are designed to identify and monitor any malicious activity or anomalies on a system or network. They can help to discover the source, scope, and impact of an attack, and provide evidence for further analysis or investigation. Detective controls include log files, security audits, intrusion detection systems, network monitoring tools, and antivirus software. In this case, the administrator used log files as a detective control to review the ransomware attack on the company's system. Log files are records of events and activities that occur on a system or network, such as user actions, system errors, network traffic, and security alerts. They can provide valuable information for troubleshooting, auditing, and forensics.

Security+ (Plus) Certification | CompTIA IT Certifications, under "About the exam", bullet point 3: "Operate with an awareness of applicable regulations and policies, including principles of governance, risk, and compliance."

CompTIA Security+ Certification Kit: Exam SY0-701, 7th Edition, Chapter 1, page 14: "Detective controls are designed to identify and monitor any malicious activity or anomalies on a system or network."

Control Types -- CompTIA Security+ SY0-401: 2.1 - Professor Messer IT ..., under "Detective Controls": "Detective controls are security measures that are designed to identify and monitor any malicious activity or anomalies on a system or network."